

# County Surveyor's Record, Douglas County, Oregon 3

Subdivision of Section 13,  
T. 29 S., R. 3 W., Willamette Meridian, Oregon

18377

CHAINS													
	No suitable tree available in sec. 13.												
	N. 0° 34' W., on the N. and S. center line of sec. 13.												
	Descend over steep NW. slope, through a recent logged area.												
8.00	Creek, 5 lks. wide, course S. 80° W.; asc. over broken SW. slope, through heavy timber and dense undergrowth.												
19.40	Gravelled road, 30 lks. wide, bears N. 80° W. and S. 80° E., 50 lks. dist. to dead end; enter old logged area with dense young timber and undergrowth.												
19.96	Point for the center S 1/16 sec. cor. of sec. 13.												
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.												
	<table style="margin: auto; border: none;"> <tr><td></td><td style="text-align: center;">C</td><td></td></tr> <tr><td style="text-align: center;">S 1/16</td><td style="text-align: center;"> </td><td style="text-align: center;">S 13</td></tr> <tr><td></td><td style="text-align: center;">C</td><td></td></tr> <tr><td></td><td style="text-align: center;">1987</td><td></td></tr> </table>		C		S 1/16		S 13		C			1987	
	C												
S 1/16		S 13											
	C												
	1987												
	from which												
	A fir, 5 ins. diam., bears N. 54° E., 42 lks. dist., mkd. X at breast height and BT at the base.												
	A fir, 8 ins. diam., bears N. 88° W., 100 lks. dist., mkd. CS 1/16 S13 BT.												
	Deposit a white "Deep-1" magnetic marker at base of stainless steel post. Alongside the corner is a steel fence post of unknown origin, firmly set.												
	The corner is on top of a spur, sloping W.												
	descend over broken NW. slope.												
37.80	Bottom of descent, bears NE. and SW.; cross creek bottom land.												
39.92	Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E. and W. center line.												
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.												
	<table style="margin: auto; border: none;"> <tr><td style="text-align: center;">T 29 S</td><td style="text-align: center;">R 3 W</td></tr> <tr><td style="text-align: center;">C¼</td><td style="text-align: center;">S 13</td></tr> <tr><td style="text-align: center;">1987</td><td></td></tr> </table>	T 29 S	R 3 W	C¼	S 13	1987							
T 29 S	R 3 W												
C¼	S 13												
1987													
	from which												
	A yew, 19 ins. diam., bears N. 12° E., 75 lks. dist., mkd. C¼ S13 BT.												
	An alder, 10 ins. diam., bears S. 3° E., 29 lks. dist., bark scribed C¼ S13 BT.												
	Deposit a white "Deep-1" magnetic marker at base of stainless steel post. Alongside the corner is a steel fence post of unknown origin, firmly set.												
	Continue across creek bottom land.												
41.30	Days creek, 15 lks. wide, course S. 70° W.												
43.60	Same Creek, 15 lks. wide, course S. 20° E.												
47.70	Same Creek, 15 lks. wide, course S. 80° W.; asc. over broken SW. slope.												