

County Surveyor's Record, Douglas County, Oregon

18378

Subdivision of Section 13,
T. 29 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
49.70	Gravelled road, 20 lks. wide, bears N. 60° E. and S. 60° W., curving SW.
53.30	Spur, slopes SW.; desc. over NW. slope.
56.90	Creek, 4 lks. wide, course S. 65° W.; asc. over SE. slope.
57.90	Gravelled road, 20 lks. wide, bears NE. and SW.
59.36	Point for the center N 1/16 sec. cor. of sec. 13. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	C N 1/16 S13 C 1987
	from which
	A fir, 6 ins. diam., bears S. 22° E., 20½ lks. dist., mkd. CN 1/16 S13 BT.
	A fir, 10 ins. diam., bears S. 16° W., 30 lks. dist., mkd. CN 1/16 S13 BT.
	Deposit a white "Deep-1" magnetic marker at base of stainless steel post. Alongside the corner is a steel fence post of unknown origin, firmly set.
	Ascend over SE. slope, through heavy timber and dense undergrowth.
78.80	The 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 1½ ins. diam., projecting 12 ins. above ground, with brass cap mkd.
	COUNTY SURVEYORS OFFICE T 29 S S 12 R S 13 3 ¼ W 1962
	from which the remains of the original bearing trees
	A madrone, 10 ins. diam., bears N. 30½° E., 16 lks. dist., bark scribed ¼ BT.
	A madrone stump, 15 ins. diam., bears S. 56° W., 12 lks. dist., no visible marks.
	and the remains of the bearing trees mkd. by Claude Kerr, Registered Professional Engineer No. 2125, in 1960
	A madrone stump, 12 ins. diam., bears S. 18° E., 9 lks. dist., with healed blaze.
	A sawed fir stump, 15 ins. diam., bears N. 50° W., 18 lks. dist., no visible marks.
	and a bearing tree mkd. by Carlson
	A cedar, 18 ins. diam., bears S. 19° W., 25 lks. dist., with scribe marks ¼ S13 BT visible on a partially healed blaze.