

County Surveyor's Record, Douglas County, Oregon

18381

Subdivision of Section 13,
T. 29 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
19.68	<p>Point for the NE 1/16 sec. cor. of sec. 13, at intersection with the E. and W. center line of the NE ¼.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 13 1987</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 30° E., 39½ lks. dist., mkd. NE 1/16 S13 BT.</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears S. 10° W., 42 lks. dist., mkd. NE 1/16 S13 BT.</p> <p style="padding-left: 40px;">Deposit a white "Deep-1" magnetic marker at base of stainless steel post. Alongside the corner is a steel fence post of unknown origin, firmly set.</p> <p>Continue over NW. slope.</p>
22.10	Days Creek, 15 lks. wide, course S. 70° W.; asc. over broken SE. slope.
27.40	Gravelled road, 15 lks. wide, bears NE. and SW.; enter scattering young timber and dense undergrowth.
37.20	Slope changes to SW.; continue to ascend.
39.37	<p>The E 1/16 sec. cor. of secs. 12 and 13, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 $\frac{S\ 12}{S\ 13}$ 1976</p> <p>from which bearing trees mkd. by Carlson .</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 3° W., 120 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 38½° W., 10½ lks. dist., with healed blaze.</p> <hr/> <p>From the N 1/16 sec. cor. of sec. 13 only, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 13 1976</p> <p>from which bearing trees mkd. by Carlson</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 13° W., 35 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears N. 63° W., 56 lks. dist., with healed blaze.</p> <p>N. 89° 51' W., on the E. and W. center line of the NE¼ of sec. 13.</p> <p>Descend over broken NW. slope, through heavy timber and dense undergrowth.</p>