

# County Surveyor's Record, Douglas County, Oregon

18383

Subdivision of Section 13,  
T. 29 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
7.70	Spur, slopes E.; desc. over broken NE. slope.
19.67	<p>Point for the NW 1/16 sec. cor. of sec. 13, at intersection with the E. and W. center line of the NW 1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 13 1987</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears East, 15 lks. dist., mkd. NW 1/16 S13 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S.73° W., 16 lks. dist., mkd. NW 1/16 S13 BT.</p> <p style="padding-left: 40px;">Deposit a white "Deep-1" magnetic marker at base of stainless steel post. Alongside the corner is a steel fence post of unknown origin, firmly set.</p> <p>Leave edge of heavy timber, bearing S. and W.; desc. over steep N. slope, through dense young timber and undergrowth.</p>
21.30	Creek, 2 lks. wide, course E.; asc. over SE. slope.
23.80	Dirt road, 15 lks. wide, bears N. 80° W. and S. 80° E.
35.40	Spur, slopes E.; desc. over steep NE. slope.
39.36	<p>The W 1/16 sec. cor. of secs. 12 and 13 monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 <math>\frac{S 12}{S 13}</math> 1976</p> <p>from which bearing trees mkd. by Carlson</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 11½° E., 22 lks. dist., with healed blaze. (Record, hemlock)</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 52½° W., 28 lks. dist., with healed blaze.</p>
	<p>From the center N. 1/16 sec. cor. of sec. 13.</p> <p>N. 88° 27' W., on the E. and W. center line of the NW¼ of sec. 13.</p> <p>Ascend over SE. slope, through dense young timber and undergrowth.</p>
1.40	Spur, slopes S.; desc. over SW. slope.
5.00	Creek, 5 lks. wide, course S.; asc. over broken NE. slope.
5.10	Dirt road, 10 lks. wide, bears N. 30° W. and S. 30° E.
18.24	<p>The NW 1/16 sec. cor. of sec. 13.</p> <p>Continue over broken NE. slope, along N. edge of a stand of heavy timber.</p>
32.90	Ravine, drains N. 55° E.; asc. over steep NE. slope.