Dependent Resurvey of a Portion of the West Boundary, T. 30 S., R. 7 W., Willamette Meridian, Oregon 18387

CHAINS	
	A fir, 12 ins. diam., bears N. 72° W., 15 lks. dist., with healed blaze.
	and the remains of the bearing trees mkd. by Howard W. Johnstone, Registered Land Surveyor No. 498, in 1961
	A sawed fir stump, 15 ins. diam., bears S. 69° E., 77 lks. dist., with scribe marks N B visible on a partially healed blaze.
	A fir, 19 ins. diam.,bears S. 37½° W., 102 lks. dist., with healed blaze.
	and a new bearing tree
	A madrone, 8 ins. diam., bears S. 61° E., 68½ lks. dist. mkd. T30S R7W S19 BT.
	N. 0° 28' W.,bet. secs. 13 and 18.
	Along W. slope, through scattering timber and dense undergrowth.
2.20	Begin descent over broken NW. slope.
11.10	Abandoned gravel road, 20 lks. wide, bears N. 30° E. and S. 30° W.
18.70	Creek, 5 lks. wide, course S. 60° E.; asc. over SE.slope.
19.45	Gravelled road, 25 lks. wide, bears N. 65° E. and S. 65° W.
19.66	Point for the S 1/16 sec. cor. of secs. 13 and 18.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam.. 18 ins. in the ground, to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	S 1/16 S 13 | S 18 1987
	from which
	A fir, 10 ins. diam., bears N. 32° E., 58 lks. dist., mkd. S 1/16 S18 BT.
	A fir, 8 ins. diam., bears N. 30° W., 17 lks. dist., mkd. S 1/16 S13 BT.
	Deposit white "DEEP-1" magnetic marker at base of stainless steel post.
	Ascend over steep SE. slope.
31.50	Spur, slopes E.;desc. over NE. slope.
35.90	Creek, 3 lks. wide, course S. 45° E.; asc. over SE. slope.
39.32	The ¼ sec. cor. of secs. 13 and 18, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1962, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 15 ins. above ground, with brass cap erroneously mkd.
	COUNTY SURVEYORS OFFICE T 30 S R R 7 S 13 | S 18 8 W ¼ W 1962