

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the West Boundary, **18389**
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 15 ins. diam., bears S. $75\frac{1}{2}^\circ$ W., 39 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears N. $59\frac{1}{2}^\circ$ W., 44 lks. dist., with healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 30 S
R 8 W R 7 W
S 12 | S 7
S 13 | S 18
1987

from which a new bearing tree

A pine, 11 ins. diam., bears S. 41° E., 39 lks. dist., mkd. T30S R7W S18 BT.

Deposit white "DEEP-1" magnetic marker at base and iron rod alongside the stainless steel post.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the survey by William H. Byars, 1882, and the
resurvey by Stephen D. Albright and Jack W. Bowder, in 1972)

From the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 30 S R 7 W
 $\frac{1}{4}$ S 18
S 19
1972

from which the remains of an original bearing tree

A cedar snag, 45 ins. diam., bears S. 19° E., 45 lks. dist., with chopped out blaze.

and bearing trees mkd. by Albright and Bowder

A fir, 13 ins. diam., bears S. 17° W., 41 lks. dist., with healed blaze.

A fir, 19 ins. diam., bears N. 51° W., $23\frac{1}{2}$ lks. dist., with healed blaze.

S. $88^\circ 19'$ W., bet. secs. 18 and 19.

Ascend over E. slope, through heavy timber and dense undergrowth.

6.80 Spur, slopes N. 10° E.; desc. over NW. slope.

10.80 Ravine, drains N.; asc. over E. slope.

17.70 Spur ridge, slopes N. 20° E.; desc. over NW. slope.

19.22 The W $\frac{1}{16}$ sec. cor. of secs. 18 and 19. monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.