

County Surveyor's Record, Douglas County, Oregon

18390 Dependent Resurvey of a Portion of the Subdivisional Lines,
 T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

W 1/16 $\frac{S\ 18}{S\ 19}$
 1972

from which bearing trees mkd. by Albright and Bowder

A fir, 12 ins. diam., bears N. 35° E., 13 lks. dist.,
 with healed blaze.

A fir, 11 ins. diam., bears S. 23½° E., 73 lks. dist.,
 with healed blaze.

S. 88° 18' W., beginning new measurement.

Descend over steep broken NW. slope.

24.21

The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the tp.

From the cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 2½ ins. diam., firmly set, with top 6 ins. below the surface of a gravelled road, 25 lks. wide, bears N. and S. 10° W., with brass cap mkd.

T 30 S
 $\frac{S\ 18\ | S\ 17}{S\ 19\ | S\ 20}$
 R 7 W
 1972

from which bearing trees mkd. by Albright and Bowder.

A fir, 10 ins. diam., bears N. 42° E., 144 lks. dist.,
 with healed blaze.

A fir, 12 ins. diam., bears S. 6° E., 99 lks. dist.,
 with healed blaze. (Record, 102 lks.)

A fir, 20 ins. diam., bears S. 45° W., 84½ lks. dist.,
 with healed blaze.

A fir, 12 ins. diam., bears N. 27½° W., 75 lks. dist.,
 with healed blaze.

The corner is located 3 lks. W. of easterly shoulder of road.

N. 0° 52' E., bet. secs. 17 and 18.

Descend over NW. slope, along gravelled road.

8.80

Leave road, bears NW. and S.; asc. over SW. slope, through scattering timber and dense undergrowth.

16.70

Spur, slopes NW.; desc. over broken N. slope.

19.79

The S. 1/16 sec. cor. of secs. 17 and 18, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, in a collar of stone, with brass cap mkd.

S 1/16
 $\frac{S\ 18\ | S\ 17}{S\ 19\ | S\ 20}$
 1972

from which the bearing trees mkd. by Albright and Bowder