

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, **18391**
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 25 ins. diam., bears S. 54 3/4° E., 99 lks. dist., with healed blaze.

A fir, 10 ins. diam., bears N. 48° W., 46 lks. dist., with healed blaze. (Record, N.49°W., 45 1/2 lks.)

N. 1° 00' E., beginning new measurement.

Descend over NW. slope.

4.00 Creek, 1 lk. wide, course S. 70° W.; asc. over steep SW. slope.

19.20 Spur, slopes W.; desc. over NW. slope.

19.85 The 1/4 sec. cor. of secs. 17 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.

T 30 S R 7 W
S 18 | S 17
1972

from which bearing trees mkd. by Albright and Bowder

A chinquapin, 12 ins. diam., bears N. 84° E., 58 1/2 lks. dist., with scribe marks 1/4 S17 BT visible on a partially healed blaze.

A fir, 10 ins. diam., bears S. 61° W., 16 1/2 lks. dist., with healed blaze.

From the cor. of secs. 7, 8, 17, and 18, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd.

T 30 S
S 7 | S 8
S 18 | S 17
R 7 W
1964

from which the original bearing trees

An oak, 16 ins. diam., bears N. 63° E., 61 lks. dist., with healed blaze.

An oak, 16 ins. diam., bears N. 34° W., 43 lks. dist., with healed blaze.

and the remains of the bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1964

A fir snag, 15 ins. diam., bears N. 18° E., 62 lks. dist., with scribe marks S8 visible on a partially healed blaze.

A root hole, bears S. 49° E., 69 lks. dist., with a cedar, 12 ins. diam., lying alongside, with scribe marks T30S R7W S17 BT visible on a partially healed blaze.

A fir, 8 ins. diam., bears S. 37° W., 57 lks. dist., with healed blaze.

and a new bearing tree

An oak, 8 ins. diam., bears S. 28° E., 209 lks. dist., mkd. T30S R7W S17 BT.