

County Surveyor's Record, Douglas County, Oregon

18394

Subdivision of Section 18,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, to solid rock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 30 S R 7 W C¼ S 18 1987</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 23° E., 20 lks. dist., mkd. C¼ S18 BT.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 5° W., 28 lks. dist., mkd. C¼ S18 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located at the base of a small rock outcrop, facing NW.</p> <p>Continue over broken NW. slope.</p>
66.70	Olalla Creek, 25 lks. wide, course S. 75° E.; asc. over gentle SW. slope.
70.30	Gravelled road, 20 lks. wide, bears E. and W.
73.60	Begin ascent over steep S. slope.
74.50	Abandoned wagon road, 10 lks. wide, bears S. 85° E. and W.
79.09	The ¼ sec. cor. of secs. 7 and 18.
	<p>From the ¼ sec. cor. of secs. 17 and 18.</p> <p>S. 88° 04' W., on the E. and W. center line of sec. 18.</p> <p>Descend over steep W. slope, through scattering timber and dense undergrowth.</p>
14.00	Gravelled road, 20 lks. wide, bears N. 15° W. and S. 15° E.
14.70	Wildcat Creek, 10 lks. wide, course N. 22° W.; asc. over steep broken E. slope.
19.53	<p>Point for the center E 1/16 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C $\frac{E 1/16}{S 18}$ C 1987</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 62° E., 21 lks. dist., mkd. CE 1/16 S18 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 48° W., 16 lks. dist. mkd. CE 1/16 S18 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Continue over steep E. slope.</p>