

County Surveyor's Record, Douglas County, Oregon

18395

Subdivision of Section 18.
T. 30 S., R.7 W., Willamette Meridian, Oregon

CHAINS														
33.90	Spur ridge, slopes N. 50° E.; desc. over NW. slope.													
39.06	The center ¼ sec. cor. of sec. 18. Continue over NW. slope.													
58.57	Point for the center W 1/16 sec. cor. of sec.18. Set a stainless steel post, 28 ins. long, 2½ ins. diam.,22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td style="padding: 0 10px;">C</td> <td style="text-align: center; border: 1px solid black; padding: 2px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">W</td> <td style="text-align: center;">1/16</td> <td style="padding: 0 5px;">C</td> </tr> <tr> <td style="padding: 0 5px;">S</td> <td style="text-align: center;">18</td> <td style="padding: 0 5px;">C</td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 2px;">1987</td> </tr> </table> </td> <td style="padding: 0 10px;">C</td> </tr> </table> </div> from which A fir, 5 ins. diam., bears N. 35° E., 24½ lks. dist., mkd. CW 1/16 S18 BT. A cedar, 6 ins. diam., bears S. 86° W., 9 lks. dist., mkd. CW 1/16 S18 BT. Deposit white "DEEP-1" magnetic marker at base of stainless steel post. Continue over NW. slope.	C	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">W</td> <td style="text-align: center;">1/16</td> <td style="padding: 0 5px;">C</td> </tr> <tr> <td style="padding: 0 5px;">S</td> <td style="text-align: center;">18</td> <td style="padding: 0 5px;">C</td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 2px;">1987</td> </tr> </table>	W	1/16	C	S	18	C	1987			C	
C	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">W</td> <td style="text-align: center;">1/16</td> <td style="padding: 0 5px;">C</td> </tr> <tr> <td style="padding: 0 5px;">S</td> <td style="text-align: center;">18</td> <td style="padding: 0 5px;">C</td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 2px;">1987</td> </tr> </table>	W	1/16	C	S	18	C	1987			C			
W	1/16	C												
S	18	C												
1987														
62.40	Creek, 10 lks. wide, course N. 60° E.; asc. over broken SE. slope.													
62.70	Gravelled road, 20 lks. wide, bears N. 55° E. and S. 55° W.													
83.02	The ¼ sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp.													
	From the E 1/16 sec. cor. of secs. 18 and 19, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. <div style="float: right; margin-top: 10px;"> <table style="font-size: small;"> <tr> <td style="padding-right: 10px;">SEE C.S. 65/72-33</td> </tr> <tr> <td>FD BTs, BOTH DOWN</td> </tr> <tr> <td>2 NEW BTs</td> </tr> <tr> <td>June 2010</td> </tr> </table> </div> <div style="text-align: center; margin-top: 10px;"> <table style="margin: auto;"> <tr> <td style="padding: 0 10px;">E 1/16</td> <td style="text-align: center; border: 1px solid black; padding: 2px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">S</td> <td style="text-align: center;">18</td> </tr> <tr> <td style="padding: 0 5px;">S</td> <td style="text-align: center;">19</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">1972</td> </tr> </table> </td> <td style="padding: 0 10px;"></td> </tr> </table> </div> from which the bearing trees mkd. by Albright and Bowder A fir, 9 ins. diam., bears N. 61° E., 12½ lks. dist., with healed blaze. A fir, 14 ins. diam., bears S. 45° W., 37 lks. dist., with healed blaze. N. 0° 40' E., on the N. and S. center line of the SE¼ of sec. 18. Descend over N. slope, through heavy timber and dense undergrowth.	SEE C.S. 65/72-33	FD BTs, BOTH DOWN	2 NEW BTs	June 2010	E 1/16	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">S</td> <td style="text-align: center;">18</td> </tr> <tr> <td style="padding: 0 5px;">S</td> <td style="text-align: center;">19</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">1972</td> </tr> </table>	S	18	S	19	1972		
SEE C.S. 65/72-33														
FD BTs, BOTH DOWN														
2 NEW BTs														
June 2010														
E 1/16	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">S</td> <td style="text-align: center;">18</td> </tr> <tr> <td style="padding: 0 5px;">S</td> <td style="text-align: center;">19</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">1972</td> </tr> </table>	S	18	S	19	1972								
S	18													
S	19													
1972														
19.77	Point for the SE 1/16 sec. cor. of sec. 18, at intersection with the E. and W. center line of the SE ¼. Set a stainless steel post, 28 ins. long, 2½ ins. diam.,22 ins. in the ground,with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td style="padding: 0 10px;">SE 1/16</td> <td style="text-align: center; border: 1px solid black; padding: 2px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">S</td> <td style="text-align: center;">18</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">1987</td> </tr> </table> </td> <td style="padding: 0 10px;"></td> </tr> </table> </div>	SE 1/16	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">S</td> <td style="text-align: center;">18</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">1987</td> </tr> </table>	S	18	1987								
SE 1/16	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">S</td> <td style="text-align: center;">18</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">1987</td> </tr> </table>	S	18	1987										
S	18													
1987														