

# County Surveyor's Record, Douglas County, Oregon

18396

Subdivision of Section 18,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 25° E., 16½ lks. dist., mkd. X at breast height and BT at the base.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 70° W., 17 lks. dist., mkd. SE 1/16 S18 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over N. slope.</p>
19.90	Small ravine, drains N. 85° E.; continue to desc. over N. slope.
35.70	Creek, 4 lks. wide, course N. 60° E.; asc. over SE. slope, through scattering timber and dense undergrowth.
39.58	The center E 1/16 sec. cor. of sec. 18.
	<p>From the S 1/16 sec. cor. of secs. 17 and 18.</p> <p>S. 88° 10' W., on the E. and W. center line of the SE¼ of sec. 18</p> <p>Descend over NW. slope, through scattering timber and dense undergrowth.</p>
2.30	Gravelled road, 20 lks. wide, bears N. 20° W. and S. 20° E.
3.70	Wildcat Creek, 10 lks. wide, course N. 10° W.; asc. over steep NE. slope.
16.70	Top of steep NE. slope; cross N. slope, through heavy timber and dense undergrowth.
19.39	The SE 1/16 sec. cor. of sec. 18.
	Continue across N. slope.
21.30	Begin descent over NW. slope.
27.50	Creek, 8 lks. wide, course N. 2° W.; asc. over NE. slope.
31.00	Spur, slopes N. 20° E.; desc. over NW. slope.
33.20	Ravine, drains N. 20° E.; asc. over E. slope.
38.81	The center S 1/16 sec. cor. of sec. 18.
	<p>From the W 1/16 sec. cor. of secs. 18 and 19.</p> <p>N. 0° 04' W., on the N. and S. center line of the SW¼ of sec. 18.</p> <p>Descend over broken NW. slope, through heavy timber and dense undergrowth.</p>
17.50	Enter scattering timber and dense undergrowth, edge bears N. 20° E. and S. 20° W.
19.72	Point for the SW 1/16 sec. cor. of sec. 18, at intersection with the E. and W. center line of the SW¼.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	SW 1/16 S 18 1987