

County Surveyor's Record, Douglas County, Oregon

18402

Corrective Dependent Resurvey of the Line
Between Sections 4 and 9,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

- 32.95 Burnt Mountain Access Road, paved surface, 30 lks. wide, bears N. 25° E. and S. 25° W.
- 38.70 Creek, 5 lks. wide, course S. 5° W.; asc. over broken SE. slope.
- 49.80 Spur, slopes S.; desc. over SW. slope.
- 54.85 Creek, 5 lks. wide, course S. 5° E.; asc. over broken SE. slope.
- 62.565 The cor. of secs. 4, 5, 8, and 9, monumented with an ironpost, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 28 S R 8 W
S 5 | S 4
S 8 | S 9
1975

from which bearing trees mkd. by Jelley

A fir, 14 ins. diam., bears N. 12° E., 117 lks. dist., with healed blaze. (Record N. 14° E.)

A fir, 12 ins. diam., bears S. 14° E., 54½ lks. dist., with healed blaze.

A fir, 16 ins. diam., bears S. 50½° W., 51 lks. dist., with healed blaze.

A fir, 14 ins. diam., bears N. 3° W., 30½ lks. dist., with healed blaze.

From this point, a local corner established by Marvin Ramsey, Registered Land Surveyor No. 404, in 1962, bears N. 62° 42' E., 0.92 chs. dist., monumented with an iron pipe, 2 ins. diam., firmly set, projecting 4 ins. above ground from which bearing trees mkd. by Ramsey

A fir, 13 ins. diam., bears N. 18° E., 10 lks. dist., with healed blaze.

A fir, 16 ins. diam., bears S. 44° E., 18 lks. dist., with healed blaze.

A fir, 16 ins. diam., bears S. 26° W., 3 lks. dist., with healed blaze.

A fir, 27 ins. diam., bears N. 31° W., 56 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, oak, myrtle, alder, and chinquapin; undergrowth, salal, poison oak, fern, arrowwood, vine maple, and Oregon grape.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the survey by Dennis Hathorn, U. S. Deputy Surveyor, in 1856, and the resurvey by Lynn M. Roseberry, Daniel L. Berry, Gordon S. Popken, and Albert J. Garrison, Cadastral Surveyors, in 1969-73)

From the ¼ sec. cor. of secs. 15 and 22, monumented with an iron post, 1½ ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.