

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, **18403**  
 T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	COUNTY SURVEYORS OFFICE $\frac{1}{4}$ S 15 S 22 1966
	from which the remains of an original bearing tree  A chinquapin stump, 25 ins. diam., bears S. 34° W., 13½ lks. dist., with a healed blaze and scribe marks BT visible on a blaze made by Byron.  and the remains of a bearing tree mkd. by Floyd C. Frear, County Surveyor, in 1936  A fir stump, 36 ins. diam., bears S. 66° E., 21 lks. dist., bark scribed CS 1/4 S BT.  and a bearing tree mkd. by James W. Byron, deputy County Surveyor, in 1957  A white fir, 9 ins. diam., bears N. 32° E., 38 lks. dist., with healed double blaze.  and bearing trees marked by Bedell  A fir, 5 ins. diam., bears N. 10½° E., 22½ lks. dist., with fragmentary scribe marks visible on partially healed double blaze.  A fir, 8 ins. diam., bears S. 39½° W., 37 lks. dist., with fragmentary scribe marks visible on partially healed blaze.  S. 89° 27' W., bet. secs. 15 and 22, marking and blazing the true line.  Descend over broken NW. slope, through heavy timber and thick undergrowth.
4.05	Creek, 45 lks. wide, course N. 30° E. from S. 5° W.; asc. over broken SE. slope.
6.25	Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.
19.91	The W 1/16 sec. cor. of secs. 15 and 22, established and recorded by Bruce A. Shaner, Registered Professional Engineer, No. 4906, in 1972, and is accepted as the corner, monumented with an iron pipe, 1¼ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.  <div style="text-align: center;">                         T 28 S R 8 W                          W 1/16 <math>\frac{S}{S}</math> 15                          S 22                          1972                     </div> from which bearing trees mkd. by Shaner  A white fir, 25 ins. diam., bears N. 67° E., 24 lks. dist., with healed blaze.  A fir, 18 ins. diam., bears S. 67½° W., 128 lks. dist., with healed blaze.
	<hr style="width: 20%; margin: auto;"/> S. 89° 27' W., beginning new measurement.  Ascend over SE. slope.
8.90	Ridge, bears N. 35° E. and S. 55° W.; desc. over broken NW. slope.