

County Surveyor's Record, Douglas County, Oregon

18404 Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

19.89

The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 1½ ins. diam., firmly set, projecting 6 ins. above ground with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 28 S R 8 W

16 | 15

21 | 22

1957

from which the remains of bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1957

A fir, 25 ins. diam., bears N. 73° E., 87½ lks. dist., with healed double blaze.

A hemlock snag, 26 ins. diam., bears S. 3 3/4° E., 60 lks. dist., with fragmentary scribing visible on partially healed blaze.

A sawed fir stump, 30 ins. diam., bears S. 45° W., 62 lks. dist., no marks visible.

and new bearing trees

A fir, 6 ins. diam., bears S. 52° E., 15 lks. dist., mkd. T 28 S R 8 W S 22 BT.

A fir, 4 ins. diam., bears S. 57° W., 20½ lks. dist. mkd. X BT.

A fir, 5 ins. diam., bears N. 69½° W., 30 lks. dist., mkd. T 28 S R 8 W S 16 BT.

Land, mountainous soil, rocky clay.

Timber, fir, hemlock, cedar, maple, oak, alder, chinquapin, and dogwood; undergrowth, poison oak, salal, vine maple, arrowwood, fern, and Oregon grape.

From the N 1/16 sec. cor. of secs. 15 and 16, monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

N 1/16

S 16 | S 15

1969

from which bearing trees mkd. by Roseberry, Berry, Popken, and Garrison

A madrone, 16 ins. diam., bears S. 58½° E., 47 lks. dist., with fragmentary scribe marks visible on partially healed blaze. (Record, S. 60½° E., 46 lks.)

A fir, 37 ins. diam., bears N. 61° W., 26 lks. dist., with healed blaze.

N. 0° 05' E., bet. secs. 15 and 16.

Ascend along broken W. slope, along W. edge of timber.

20.01

Point for the cor. of secs. 9, 10, 15, and 16, at proportionate distance.

From this point, the cor. of secs. 9, 10, 15, and 16, reestablished by Roseberry, Berry, Popken, and Garrison, in 1969-73, bears S. 64° 31' W., 0.38 chs, dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. as described in the official record, from which the remains of the bearing trees mkd. by Roseberry, Berry, Popken, and Garrison: