

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, **18405**
 T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A root hole, bears N. 58° E., 69 lks. dist., with down cedar alongside, 10½ ins. diam., with healed blaze.

A fir, 18 ins. diam., bears S. 42° E., 24 lks. dist., with healed blaze. (Record, S. 45 3/4° E.)

A root hole, bears S. 13° W., 50 lks. dist., with down fir alongside, 14 ins. diam., with healed blaze. (Record, S. 10¼° W., 48½ lks.)

A root hole, bears N. 12½° W., 59 lks. dist., with down fir alongside, 19 ins. diam., with healed blaze. (Record, N. 26½° W.)

Upon investigation of the area around this corner, it shows a large area slumping, which includes all of the bearing trees. The NE., NW., and SW. bearing trees have tipped over due to the movement of the ground, but have maintained proper position. Also, the record topography call of a wire fence extending N. and S. from the corner, is now east of the corner approximately 0.34 chs. dist.

Remove the iron post, destroy the marks on the bearing trees and at the true corner point

Reset the iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 28 S R 8 W
 S 9 | S 10
 S 16 | S 15
 1969

from which

A stainless steel post, 28 ins. long, 2½ ins. diam., set 26 ins. in the ground for a reference monument, bears N. 20° E., 150 lks. dist., with brass cap mkd. T28S R8W S10 RM, and an arrow pointing to the corner.

A stainless steel post, 28 ins. long, 2½ ins. diam., set 28 ins. in the ground for a reference monument, bears N. 50° W., 150 lks. dist., with brass cap mkd. T28S R8W S9 RM, and an arrow pointing to the corner.

Deposit white "DEEP-1" magnetic marker at base of the stainless steel post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, and alder; undergrowth, arrowwood, poison oak, salal, and Oregon grape.

From the ¼ sec. cor. of secs. 10 and 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.

T 28 S R 8 W
 ¼ S 10
 S 15
 1969

from which bearing trees mkd. by Roseberry, Berry, Popken, and Garrison

A chinquapin, 7 ins. diam., bears S. 33° W., 16 lks. dist., with scribe marks ¼ S15 BT visible on partially healed blaze.