

County Surveyor's Record, Douglas County, Oregon

18408

Dependent Resurvey of a Portion of the Boundaries
of Donation Land Claim No. 41,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	At the corner point Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd. T 28 S R 8 W S 15 C 41 1987 Deposit white "DEEP-1" magnetic marker at base of stainless steel post. N. 0° 25' E., on the W. bdy. of Claim No. 41, marking and blazing the true line. Descend over NE. slope, through scattering timber and open pasture.
1.00	Tenmile Creek, 20 lks. wide, course SE.; asc. over SW. slope.
24.85	Coos Bay Wagon Road, paved surface, 30 lks. wide, bears N. 40° W. and S. 40° E.
25.81	Intersect the E. and W. center line of section 15.
31.80	Power transmission lines, bear E. and W.
34.35	Power transmission lines, bears N. 85° W. and S. 85° E.
38.82	Point for the NW. cor. of Donation Land Claim No. 41, at proportionate position, determined by the Grant boundary method; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. T 28 S R 8 W S 15 C 41 1987 from which A white fir, 30 ins. diam., bears N. 15 3/4° E., 35 lks. dist., mkd. C 41 BT. A fir, 17 ins. diam., bears S. 49° E., 36 lks. dist., mkd. C 41 BT. Deposit white "DEEP-1" magnetic marker at base of stainless steel post.
	S. 89° 35' E., on the N. bdy. of Claim No. 41. Descend over SE. slope, through heavy timber and moderate undergrowth.
2.35	Intersect the N. and S. center line of sec. 15 Point for the crossing closing corner, hereinafter described. Descend over SE. slope.
5.20	Creek, 4 lks. wide, course S. from N. 30° E.; asc. over NW. slope
12.05	Spur, slopes S. 40° W.; desc. over SE. slope.
19.75	Power transmission lines, bear N. 50° E. and S. 50° W.