


# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 15, T. 28 S., R. 8 W.  
Willamette Meridian, Oregon

18411

**CHAINS**

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.



from which

A white fir, 12 ins. diam., bears N. 58° E., 18 lks. dist. mkd. S 15 CCC BT.

A white fir, 18 ins. diam., bears N. 59 ¾° W., 16 lks. dist., mkd. S 15 CCC BT.


Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point the NW. cor. of Donation Land Claim No. 41, bears N. 89° 35' W., 2.35 chs. dist., hereinbefore described.

Ascend over SE. slope.

60.12 Point for the center N 1/16 sec. cor. of sec. 15.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A white fir, 17 ins. diam., bears S. 78° W., 14 lks. dist., mkd. CN 1/16 S 15 BT.

A fir, 16 ins. diam., bears N. 18° W., 8 lks. dist., mkd. CN 1/16 S 15 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.


Ascend over SE. slope.

68.45 Spur, slopes N. 80° E.; desc. over N. slope.

74.05 Creek, 4 lks. wide, course S. 75° E.; asc. over SE. slope.

80.15 The 1/4 sec. cor. of secs. 10 and 15.

From the ¼ sec. cor. of secs. 14 and 15, perpetuated and recorded by Bruce A. Shaner, Registered Professional Engineer No. 4906, in 1972, monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.



from which the remains of an original bearing tree

A rotted, sawed fir stump, size indeterminate, bears S. 5° E., 22 lks. dist., with scribe marks BT and a chaining notch visible on opened blaze.