

County Surveyor's Record, Douglas County, Oregon

18412

Subdivision of Section 15, T. 28 S., R. 8 W.,
Willamette Meridian, Oregon

CHAINS										
	and bearing trees mkd. by Shaner									
	A fir, 19 ins. diam., bears S. 31 3/4° E., 63 lks. dist., with healed blaze.									
	A fir, 23 ins. diam., bears N. 88 1/2° W., 70 lks. dist., with healed blaze.									
	From this point, the 1/4 sec. cor. of secs. 11 and 14, designated as a third order horizontal control station by the Douglas County Surveyor's Office, in 1984, at latitude 43° 08' 31.1" N., longitude 123° 36' 41.4" W., bears N. 45° 23' 30" E., 57.06 chs. dist., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T28S R8W 1/4 S11 S14 1970.									
	S. 89° 30' W., on the E. and W. center line of sec. 15.									
	Ascend over NE. slope, through scattering timber and light undergrowth.									
1.20	Ridge, bears N. 20° W. and S. 35° E.; desc. over NW. slope.									
10.45	Ravine, drain S. 30° W.; asc. over SE. slope, through open pasture.									
20.05	Point for the center E 1/16 sec. cor. of sec. 15.									
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.									
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">C</td> <td style="text-align: center; border-bottom: 1px solid black; padding: 0 10px;">E 1/16</td> <td style="padding: 0 10px;">C</td> </tr> <tr> <td></td> <td style="text-align: center; padding: 0 10px;">S 15</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center; padding: 0 10px;">1987</td> <td></td> </tr> </table>	C	E 1/16	C		S 15			1987	
C	E 1/16	C								
	S 15									
	1987									
	from which									
	A cedar, 12 ins. diam., bears S. 61 3/4° W., 374 lks. dist., mkd. CE 1/16 S 15 BT.									
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 41 1/2° W., 380 lks. dist., with brass cap mkd. CE 1/16 S15 RM 1987, and an arrow pointing to the corner.									
	Deposit white "DEEP-1" magnetic marker at base of the stainless steel post.									
	Ascend over SE. slope.									
23.40	Coos Bay Wagon Road, paved surface, 30 lks. wide, bears N. 20° E. and S. 30° W.									
28.80	Spur, slopes S. 10° W.; desc. over SW. slope.									
40.10	The center 1/4 sec. cor. of sec. 15.									
	Descend over SW. slope.									
42.53	Intersect the W. bdy. of Donation Land Claim No. 41.									
43.45	Coos Bay Wagon Road, paved surface, 30 lks. wide, bears N. 40° W. and S. 40° E.									
46.15	Tenmile Creek, 15 lks. wide, course S. 20° E.; asc. over NE. slope.									