

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 15, T. 28 S., R. 8 W., **18413**
Willamette Meridian, Oregon

CHAINS	
60.03	<p>Point for the center W 1/16 sec. cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $C \frac{W \ 1/16}{S \ 15} C$ <p>1987</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 5 ins. diam., bears N. 79½° E., 48 lks. dist., mkd. X BT.</p> <p style="margin-left: 40px;">A fir, 10 ins. diam., bears N. 44¼° W., 22 lks. dist., mkd. CW 1/16 S 15 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over NE. slope.</p>
68.10	Spur, slopes N. 25° E.; desc. over broken NW. slope.
72.70	Ravine, drains N. 35° W.; asc. over broken NE. slope.
78.90	Spur, slopes N.; desc. over NW. slope.
79.96	<p>The ¼ sec. cor. of secs. 15 and 16, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $T \ 28 \ S \ R \ 8 \ W$ $S \ 16 \ \begin{array}{c} \uparrow \\ \frac{1}{4} \end{array} \ S \ 15$ <p>1969</p> </div> <p>from which bearing trees marked by Roseberry, Berry, Popken, and Garrison</p> <p style="margin-left: 40px;">A hemlock, 15 ins. diam., bears N. 32½° E., 40 lks. dist., with fragmentary scribing visible on partially healed blaze. (Record, fir.)</p> <p style="margin-left: 40px;">A chinquapin, 15 ins. diam., bears N. 15 ¾° W., 47 lks. dist., with fragmentary scribing visible on partially healed blaze.</p>
7.90	<p>From the center E 1/16 sec. cor. of sec. 15.</p> <p>N. 0° 05' W., on the N. and S. center line of the NE¼ of sec. 15</p> <p>Ascend over SE. slope, through open pasture.</p> <p>Coos Bay Wagon Road, paved surface, 30 lks. wide, bears N. 30° E. and S. 30° W.</p>
12.25	Power transmission lines, bear N. 50° E. and S. 50° W.
12.65	<p>Intersect the N. bdy. of Donation Land Claim No. 41.</p> <p>Point for the crossing closing cor. of the N. and S. center line of the NE¼ of sec. 15, on the N. bdy. of Claim No. 41.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>