

County Surveyor's Record, Douglas County, Oregon

18419

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R 1 W., Willamette Meridian, Oregon

CHAINS																	
	<p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, a point established and recorded as the $\frac{1}{4}$ sec. cor. of secs. 9 and 10 by Thomas E. Shrum, Jr., Registered Engineer No. 4287, in 1966, bears N. $70^{\circ} 37' 00''$ W., 0.250 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, with a $2\frac{1}{2}$ in. diam. aluminum cap mkd. TWP 25S R1W $\frac{1}{4}$ 9 10 RE 4287, from which bearing tree mkd. by Shrum:</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 40° E., 48 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A hemlock, 11 ins. diam., bears N. $46\frac{1}{2}^{\circ}$ W., 12 lks. dist., with scribe marks S9 $\frac{1}{4}$ BT visible on open blaze.</p> <p>This position was established using improper control: therefore is not used in this resurvey.</p> <p>Ascend over SE. slope.</p>																
49.30	Gravelled road, 25 lks. wide, bears N. 80° E. and S. 75° W.																
57.90	Ridge, bears NE. and SW.; desc. over NW. slope, changing to NE. slope.																
69.20	Gravelled road, 30 lks. wide, bears NE. and SW.																
80.450	<p>Point for the cor. of secs. 3, 4, 9, and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="4">T 25 S R 1 W</td> </tr> <tr> <td style="border-right: 1px solid black; border-bottom: 1px solid black;">S 4</td> <td style="border-bottom: 1px solid black;">S 3</td> <td colspan="2"></td> </tr> <tr> <td style="border-right: 1px solid black;">S 9</td> <td>S 10</td> <td colspan="2"></td> </tr> <tr> <td colspan="4" style="text-align: center;">1987</td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A cedar, 5 ins. diam., bears N. 17° E., 35 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A cedar, 17 ins. diam., bears S. $62\frac{1}{2}^{\circ}$ E., 42 lks. dist., mkd. T25S R1W S10 BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. $61\frac{1}{4}^{\circ}$ W., 47 lks. dist., mkd. T25S R1W S9 BT.</p> <p style="padding-left: 40px;">A cedar, 8 ins. diam., bears N. $50\frac{1}{4}^{\circ}$ W., 45 lks. dist., mkd. T25S R1W S4 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, a point established and recorded as the cor. of secs. 3, 4, 9, and 10, by Thomas E. Shrum, Jr. Registered Engineer No. 4287, in 1966, bears S. $78^{\circ} 40' 00''$ W., 0.730 chs. dist., monumented with an iron post, 1 in. diam., loosely set, projecting 20 ins. above ground, with a $2\frac{1}{2}$ in. diam. aluminum cap mkd. USPL PROPERTY COR TWP 25S R1W 3 4 9 10 RE 4287, from which bearing trees mkd. by Shrum:</p>	T 25 S R 1 W				S 4	S 3			S 9	S 10			1987			
T 25 S R 1 W																	
S 4	S 3																
S 9	S 10																
1987																	