

County Surveyor's Record, Douglas County, Oregon

18421

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 1 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">A hemlock, 3 ins. diam., bears N. 45° W., 21½ lks. dist., mkd. X BT.</p> <p>From this corner, a control point at latitude 43° 25' 21.81" N. and longitude 122° 47' 01.66" W., established in conjunction with this survey, bears N. 79° 09' 42" W., 10.530 chs. dist., monumented with a finned aluminum rod, 36 ins. long, 3/4 in. diam. firmly set 36 ins. in the ground, in a collar of concrete, with aluminum cap, 2½ ins. diam., mkd. ECI G 1347 1987.</p> <p>N. 89° 59' 00" W., bet. secs. 3 and 10.</p> <p>Ascend over broken SE. slope, through heavy timber and dense undergrowth.</p>
1.00	Gravelled road, 30 lks. wide, bears N. 30° W. and S. 10° W.
3.15	Gravelled road, 30 lks. wide, bears N. 10° W. and S. 25° E.
39.190	<p>Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 25 S R 1 W</p> <p>¼ $\frac{S 3}{S 10}$</p> <p>1987</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 4 ins. diam., bears S. 4° E., 23 lks. dist., mkd. ¼ S10 BT.</p> <p style="margin-left: 40px;">A fir, 4 ins. diam., bears North, 40½ lks. dist., mkd. ¼ S3 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, a point established and recorded as the ¼ sec. cor. of secs. 3 and 10, by Thomas E. Shrum, Jr., Registered Engineer No. 4287, in 1966, bears S. 84° 25' 00" W., 0.380 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with a 2 in. diam. aluminum cap mkd. TWP 25S RLW ¼ 3 10 RE 4287, from which the remains of bearing trees mkd. by Shrum:</p> <p style="margin-left: 40px;">A sawed fir stump, 40 ins. diam., bears N. 33° E., 78 lks. dist., with scribe marks S3 BT visible on open blaze.</p> <p style="margin-left: 40px;">A fir stump, 9 ins. diam., bears S. 32° W., 45 lks. dist., no marks visible.</p> <p>This position was established using improper control; therefore is not used in this resurvey.</p> <p>Ascend over broken SE slope.</p>
44.70	Gravelled road, 15 lks. wide, bears N. 60° E. and S. 60° W.
57.90	Ridge, bears N. 60° E. and SW.; desc. over broken NW. slope, changing to SW. slope.