

# County Surveyor's Record, Douglas County, Oregon

**18422**

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 25 S., R. 1 W., Willamette Meridian, Oregon

CHAINS	
58.05	Gravelled road, 25 lks. wide, bears N. 40° E. and S. 50° W.
78.380	<p>The cor. of secs. 3, 4, 9, and 10.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, pine, yew, hemlock, cedar, alder, madrone, chinquapin, and dogwood; undergrowth, blackberry, salmonberry, thimbleberry, manzanita, ceanothus, huckleberry, arrowwood, hazel, vine maple, salal, Oregon grape, and ferns.</p>
24.50	<p>N. 2° 06' 00" E., bet. secs. 3 and 4.</p> <p>Descend over NE. slope, changing to NW. slope, through heavy timber and dense undergrowth.</p> <p>Trapper Creek, 8 lks. wide, course N. 50° E.; asc. over SE. slope.</p>
33.30	Gravelled road, 30 lks. wide, bears N. 70° E. and S. 70° W.
40.225	<p>The ¼ sec. cor. of secs. 3 and 4, monumented with the remains of the original corner tree, a sawed fir stump, 8 ft. high, 13 ins. diam., with scribe marks ¼ S visible on W. face, from which the remaining original bearing tree:</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears N. 54° E., 12 lks. dist., with fragmentary scribe marks visible on opened blaze.</p> <p>and a reference monument and a bearing tree mkd. by Jelley</p> <p style="padding-left: 40px;">An iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, bears N. 25° E., 13½ lks. dist., with brass cap mkd. ¼ S3 RM 1978 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A sawed fir stump, 15 ins. diam., bears N. 47° W., 35 lks. dist., with scribe marks ¼ S4 BT visible on open blaze.</p> <p>Land, mountainous. Soil, rocky clay Timber, maple, fir, hemlock, yew, alder, chinquapin, cedar, dogwood, and madron; undergrowth, arrowwood, hazel, manzanita, ceanothus, Oregon grape, salal, blackberry, huckleberry, salmonberry, vine maple, ferns, and young timber.</p>
1.95	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89° 34' 00" W., bet. secs. 4 and 9.</p> <p>Ascend over broken NE. slope, through heavy timber and dense undergrowth.</p> <p>Spur, slopes N.; desc. over broken NW. slope.</p>
15.70	Trapper Creek, 5 lks. wide, course N. 10° E.; asc. over broken NE. slope.
39.300	The ¼ sec. cor. of secs. 4 and 9, monumented with an iron post 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 25 S R 1 W  
¼  $\frac{S 4}{S 9}$   
1978