

County Surveyor's Record, Douglas County, Oregon

18426 Dependent Resurvey of a Portion of the Subdivisionsal Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	(Restoring the survey by William Byars in 1874, the survey and resurvey by Alonzo Gesner and Elmer O. Worrick in 1894, and the retracement by George S. Pershin in 1896)
	Beginning at the cor. of secs. 10 and 15 only, perpetuated by person(s) unknown and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1956, monumented with an iron post, 1 ½ ins. diam., firmly set, projecting 24 ins. above ground, with iron cap mkd. S10 S15 S16, from which the remains of bearing trees mkd. by Gesner and Worrick:
	A cedar, 45 ins. diam., bears N. 81° E., 39 lks. dist., with old axe marks visible.
	A maple, 48 ins. diam., bears S. 34½° W., 22 lks. dist., no marks remaining on open, decayed blaze. (Record, S. 44½° W.)
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 S R 9 W 16 $\frac{S 10}{S 15}$ 1987
	from which new bearing trees
	A fir, 7 ins. diam., bears N. 6 3/4° E., 124 lks. dist., mkd. T22S R9W S10 BT.
	A fir, 23 ins. diam., bears S. 68° E., 41 lks. dist., mkd. T22S R9W S15 BT.
	Deposit a white "DEEP-1" magnetic marker at the base and local iron post alongside the corner post.
	The corner is located 45 lks. N. of a creek, 1 lk. wide, course N. 80° E.
	N. 0° 14' 00" W., bet. secs. 10 and 16.
	Ascend over SE. slope, through heavy timber and dense undergrowth.
2.740	Point for the closing cor. of secs. 9 and 16, hereinafter described. Also, top of ascent, slopes E., continue along broken E. slope.
	Between secs. 9 and 10.
7.20	Creek, 5 lks. wide, course N. 40° E.
8.30	Creek, 1 lk. wide, course N. 80° E.
16.90	West shore of Burchard Lake, bears N. 15° W, and S. 20° E., thence across lake.
23.50	East shore of Burchard Lake, bears N. 15° W. and S. 20° E.; asc. over SW. slope
35.90	Top of ascent, slopes W.; desc. over NW. slope.
39.185	Point for the ¼ sec. cor. of sec. 10 only at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.