

County Surveyor's Record, Douglas County, Oregon

18427

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S. R. 9 W., Willamette Meridian, Oregon

CHAINS	T 22 S R 9 W $\frac{1}{4}$ S 10 1987
	from which A fir, 18 ins. diam., bears N. 53° E., 52 lks. dist., mkd. X BT. A fir 16 ins. diam., bears S. 79° E., 16 lks. dist., mkd. $\frac{1}{4}$ S10 BT. Deposit a white "DEEP-1" magnetic marker at the base of the iron post. Descend over NW. slope.
42.105	Point for the $\frac{1}{4}$ sec. cor. of sec. 9 only. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 S R 9 W $\frac{1}{4}$ S 9 1987 </div> from which A fir, 12 ins. dia., bears S. 5¾° W., 46½ lks. dist., mkd. $\frac{1}{4}$ S9 BT. A fir, 14 ins. diam., bears N. 35° W., 124 lks. dist., mkd. X BT. Deposit a white "DEEP 1" magnetic marker at the base of the iron post.
43.50	Purdy Creek, 20 lks. wide, course S. 40° W.; asc. over SE. slope.
45.45	Top of ascent, slopes E.; desc. over NE. slope.
46.80	Purdy Creek, 20 lks. wide, course S. 20° E.; thence up creek.
47.75	Leave Purdy Creek; asc. Over SE. slope.
57.65	Creek, 1 lk. wide, course S. 25° E.; asc. over SE. slope.
61.65	Purdy Creek, 30 lks. wide, course S. 30° E.; asc. over SW. slope.
78.370	Point for the cor. of secs. 4 and 9 only, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 S R 9 W $\frac{S 4}{S 9}$ S 10 1987 </div> from which A fir, 14 ins. diam., bears S. 5½° W., 30½ lks. dist., mkd. T22S R9W S9 BT. A fir, 11 ins. diam., bears N. 51° W., 24 lks. dist., mkd. T22S R9W S4 BT.