

County Surveyor's Record, Douglas County, Oregon

18428

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS							
	<p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Land, mountainous. Soil, clay and rock. Timber, fir, cedar, alder, maple, hemlock, and dogwood; undergrowth, huckleberry, salmonberry, vine maple, Orgeon grape, salal, ferns, and grasses.</p>						
2.135	<p>N. 0° 14' 00" W., bet. secs. 4 and 10.</p> <p>Ascend over SW. slope, through heavy timber and dense undergrowth.</p> <p>Point for the closing cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 22 S R 9 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">S 4</td> <td style="border-left: 1px solid black; padding: 0 5px; text-align: center;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 2px;">S 3</td> <td style="padding: 0 2px;">CC</td> </tr> <tr> <td style="padding: 0 2px;">S 10</td> <td></td> </tr> </table> </td> </tr> </table> <p>1987</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 11 ins. diam., bears N. 6¾° E., 35 lks. dist., mkd. T22S R9W S3 CC BT.</p> <p style="margin-left: 40px;">A fir, 18 ins. diam., bears S. 65¼° E., 61 lks. dist., mkd. T22S R9W S10 CC BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Between secs. 3 and 4.</p>	S 4	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 2px;">S 3</td> <td style="padding: 0 2px;">CC</td> </tr> <tr> <td style="padding: 0 2px;">S 10</td> <td></td> </tr> </table>	S 3	CC	S 10	
S 4	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 2px;">S 3</td> <td style="padding: 0 2px;">CC</td> </tr> <tr> <td style="padding: 0 2px;">S 10</td> <td></td> </tr> </table>	S 3	CC	S 10			
S 3	CC						
S 10							
3.45	<p>Rocky spur, slopes W.; asc. over broken SW. slope.</p>						
14.60	<p>Rocky spur, slopes W.; desc. over broken NW. slope.</p>						
20.45	<p>Ravine, drains N. 85° W.; asc. over SW. slope.</p>						
39. 185	<p>The ¼ sec. cor. of sec. 4 only, perpetuated and recorded by Vernon W. Hosford, Registered Land Surveyor No. 253, in 1954, monumented with an iron pipe, 1 in. diam., firmly set, projecting 2 ins. above ground, from which the remains of an original bearing tree:</p> <p style="margin-left: 40px;">A badly decayed fir stump, size indeterminate, bears S. 72° W., 35 lks. dist., with reverse scribe marks ¼ visible on decayed fir slab.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 22 S R 9 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">S 4</td> <td style="border-left: 1px solid black; padding: 0 5px; text-align: center;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 2px;">¼</td> <td></td> </tr> </table> </td> </tr> </table> <p>1987</p> </div>	S 4	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 2px;">¼</td> <td></td> </tr> </table>	¼			
S 4	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 2px;">¼</td> <td></td> </tr> </table>	¼					
¼							