

# County Surveyor's Record, Douglas County, Oregon

18429

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS							
	<p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. <math>25\frac{1}{4}^{\circ}</math> W., 26 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. <math>64\frac{1}{2}^{\circ}</math> W., <math>31\frac{1}{2}</math> lks. dist., Mkd. <math>\frac{1}{4}</math> S4 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located 1 ch. W. of a dirt road, 25 lks. wide, bears N. <math>80^{\circ}</math> E. and S. <math>15^{\circ}</math> W.</p>						
	<hr style="width: 20%; margin: 0 auto;"/>						
	<p>N. <math>0^{\circ} 42' 30''</math> E., beginning new measurement.</p> <p>Ascend over SW. slope, through heavy timber and dense undergrowth.</p>						
0.50	Spur, slopes N. $70^{\circ}$ W.; desc. over N. slope.						
3.540	Point for the $\frac{1}{4}$ sec. cor. of sec. 3 only. No monument established.						
7.25	Creek, 1 lk. wide course N. $80^{\circ}$ W.; asc. over SW. slope.						
18.00	Dirt road, 20 lks. wide, bears N. $30^{\circ}$ W. and S. $60^{\circ}$ E.						
20.50	Same road, 20 lks. wide, bears N. $15^{\circ}$ E. and S. $25^{\circ}$ W.						
21.000	<p>Point for the N <math>1/16</math> sec. cor. of sec. 4 only.</p> <p style="padding-left: 40px;">Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding-left: 80px;"> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">N <math>1/16</math></td> <td style="padding: 0 5px;"> </td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 4</td> <td style="padding: 0 5px;"> </td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">1987</td> </tr> </table> </div>	N $1/16$		S 4			1987
N $1/16$							
S 4							
	1987						
	<p>from which</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. <math>42\frac{1}{2}^{\circ}</math> W., <math>40\frac{1}{2}</math> lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. <math>2^{\circ}</math> W., <math>32\frac{1}{2}</math> lks. dist., mkd. N <math>1/16</math> S4 BT.</p> <p>The corner is located on the westerly edge of a dirt road, 20 lks. wide, bears N. <math>40^{\circ}</math> E. and S. <math>10^{\circ}</math> W.</p> <p>Continue over broken W. slope, changing to SW. slope.</p>						
32.60	Dirt road, 20 lks. wide, bears N. $65^{\circ}$ W. and S. $70^{\circ}$ E.						
35.75	Dirt road, 20 lks. wide, bears E. and S. $80^{\circ}$ W.						
39.505	<p>The closing cor. of secs. 3 and 4, perpetuated by person(s) unknown and recorded by Vernon W. Hosford, Registered Land Surveyor No. 253, in 1954, monumented with an iron post, <math>1\frac{1}{2}</math> ins. diam., firmly set 6 ins. below ground, with iron cap makd. S3 S4 S33, from which the remains of an original bearing tree:</p> <p style="padding-left: 40px;">A decayed fir stump, 38 ins. diam., bears S. <math>24^{\circ}</math> E., 66 lks. dist., with scribe mark T visible on opened blaze.</p> <p>At the corner point</p>						