

County Surveyor's Record, Douglas County, Oregon

18430

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 21 S R 9 W
S 33
S 4 | S 3
T 22 S
CC
1987

from which new bearing trees

A fir, 11 ins. diam., bears S. 10 3/4° E., 84½ lks. dist., mkd. T22S R9W S3 CC BT.

A fir, 15 ins. diam., bears S. 61½° W., 55 lks. dist., mkd. T22S R9W S4 CC BT.

Deposit a white "DEEP-1" magnetic marker at the base and the iron post alongside the stainless steel post.

The corner is located 130 lks. S. of a ridge, bears E. and W.

From this corner, the cor. of secs. 33 and 34 only, T 21 S., R. 9 W., bears S. 87° 43' 00" E., 3.530 chs. dist., perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1971, monumented with an iron post, 1½ ins. diam., firmly set, projecting 14 ins. above ground (alongside of which is an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground), with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 21 S R 9 W
S 33 | S 34
S 3
1971

from which the remains of an original bearing tree

A sawed fir stump, 36 ins. diam., bears N. 88° W., 59 lks. dist., with scribe marks T21 visible on opened blaze.

and bearing trees mkd. by Powell

An alder, 10 ins. diam., bears N. 24° E., 19½ lks. dist., with healed blaze.

A fir, 6 ins. diam., bears S. 80° E., 10½ lks. dist., with healed blaze.

A fir, 13 ins. diam., bears N. 53° W., 6 lks. dist., with healed blaze.

and a new bearing tree

A fir, 10 ins. diam., bears N. 18¼° E., 42 lks. dist., mkd. T21S R9W S34 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, alder, cedar, maple, and chinquapin; undergrowth huckleberry; salmonberry, salal, vine maple, poison oak, Oregon grape, ferns, and grasses.