

# County Surveyor's Record, Douglas County, Oregon

**18432** Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{r} W \ 1/16 \ S \ 9 \\ \quad \quad \quad S \ 16 \\ \quad \quad \quad 1987 \end{array}</math> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 7 3/4° E., 32½ lks. dist., mkd. W 1/16 S9 BT.</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears N. 85° W., 54½ lks. dist., mkd. W 1/16 S9 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, a control point established by the Doppler method of global positioning under Group 1281 in 1985, bears N. 3° 21' 15" W., 178.780 chs. dist., monumented with an aluminum cap, 2½ ins. diam., firmly set in concrete, with top mkd. EC1 GP 1281 1985 and a triangle.</p> <p>Continue ascent over NW. slope.</p>
21.10	Spur, slopes S. 55° W.; desc. over broken SE. slope.
33.35	Ravine, drains S. 40° W.; asc. over NW. slope.
39.255	<p>The ¼ sec. cor. of secs. 9 and 16, determined at record bearing and distance from the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A sawed fir stump, 40 ins. diam., bears N. 20½° E., 55 lks. dist., with scribe marks BT visible on opened blaze</p> <p style="padding-left: 40px;">A sawed fir stump, 60 ins. diam., bears S. 20½° W., 10 lks. dist., with scribe marks S BT visible on opened blaze</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. dia., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{r} T \ 22 \ S \ R \ 9 \ W \\ \quad \quad \quad S \ 9 \\ \quad \quad \quad \frac{1}{4} \ S \ 16 \\ \quad \quad \quad 1987 \end{array}</math> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 26¼° E., 22 lks. dist., mkd. ¼ S9 BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 49¼° E., 28½ lks. dist., mkd. ¼ S16 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
	<hr style="width: 20%; margin: 0 auto;"/> <p>N. 89° 40' 00" E., beginning new measurement.</p> <p>Ascend over NW. slope, changing to SW. slope.</p>
7.75	Ridge, bears N. 40° W. and S. 45° E.; desc. over NE. slope.
43.45	Dirt road, 15 lks. wide, bears N. 20° W. and S. 15° W., in a curve.