

# County Surveyor's Record, Douglas County, Oregon

18433

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 9 W., Willamette Meridian, Oregon

**CHAINS**

44.665

Intersect the W. bdy. of sec. 10, and point for the closing cor. of secs. 9 and 16.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 S  
CC  $\frac{S 9}{S 16}$  | S 10  
R 9 W  
1987

from which

A fir, 11 ins. diam., bears S. 36° W., 13½ lks. dist., mkd. T22S R9W S16 CC BT.

A fir, 6 ins. diam., bears N. 80° W., 33½ lks. dist., mkd. X BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

From this point, the original closing cor. of secs. 9 and 16, bears N. 89° 40' 00" E., 0.070 chs. dist., perpetuated by person(s) unknown, and further perpetuated and recorded by Vernon Tracy, Deputy County Surveyor, in 1968, monumented with an iron post, 1½ ins. diam., firmly set, projecting 14 ins. above ground (alongside of which is an iron post, 1½ ins. diam., firmly set, projecting 2 ins. above ground, with iron cap mkd. S9 S10 S16), with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 22 S  
 $\frac{S 9}{S 16}$  | CC  
R 9 W  
1968

from which the remains of the original bearing trees

A sawed fir stump, 28 ins. diam., bears N. 66 ¾° E., 81 lks. dist., with healed blaze. (Record, N. 65° E.)

A shattered fir stump, 40 ins. diam., bears S. 40° W., 184 lks. dist., no marks visible.

A fir snag, 29 ins. diam., bears N. 21° W., 176½ lks. dist., with scribe marks T22S R9W S9 BT visible on decayed blaze. (Record, 148 lks.)

and bearing trees mkd. by Tracy

An alder, 11 ins. diam., bears S. 45° W., 86½ lks. dist., no marks visible on partially healed blaze.

A fir, 18 ins. diam., bears N. 84° W., 103 lks. dist., with healed blaze.

This corner is now amended.

From this same point, the cor. of secs. 10 and 15 only, bears S. 0° 14' 00" E., 2.740 chs. dist., hereinbefore described.