

County Surveyor's Record, Douglas County, Oregon

18439

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

- 20.25 Fence corner, fences extending N., S. 20° E., and W.
- 32.45 Spur, slopes N. 70° E.; desc. over NW. slope.
- 39.960 The ¼ sec. cor. of secs. 31 and 32, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1958, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 12 ins. above ground with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 28 S
S | S
¼ 31 | 32
R 6 W
1958

from which the remains of an original bearing tree

An oak snag, 27 ins. diam., bears N. 67° E., 82 lks. dist., with scribe mark S visible on opened blaze.

and bearing trees mkd. by Byron

A fir, 22 ins. diam., bears N. 23 ¾° E., 77 lks. dist., with healed, double blaze.

A fir, 21 ins. diam., bears N. 29¼° W., 62 lks. dist., with healed, double blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, madrone, maple, alder, dogwood, yew, pine, and cherry; undergrowth, Oregon grape, salal, hazel, arrowwood, salmonberry, blackberry, huckleberry, ferns. manzanita, poison oak, and young timber.

Subdivision of Section 31,
T. 28 S., R. 6 W., Willamette Meridian, Oregon

- 20.175 From the ¼ sec. cor. of secs. 6 and 31, on the S. bdy. of the Tp. N. 0° 01' 00" E., on the N. and S. center line of sec. 31.
Descend over broken N. slope, changing to NE. slope.
Point for the center S 1/16 sec. cor. of sec. 31.
Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

C
S 1/16 | S 31
C
1987

from which

An oak, 8 ins. diam., bears N. 75 ¾° E., 20 lks. dist., mkd. CS 1/16 S31 BT.

A fir, 40 ins. diam., bears S. 76 ¾° W., 60 lks. dist., mkd. CS 1/16 S31 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Descend over NE. slope.