

County Surveyor's Record, Douglas County, Oregon

18442

Subdivision of Section 31,
T. 28 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which the remains of a bearing tree mkd. by Stewart</p> <p style="padding-left: 40px;">A root hole, bears N. 6½° E., 45 lks. dist., with down fir alongside, size indeterminate, no marks visible.</p> <p>and bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A madrone, 20 ins. diam., bears S. 61° E., 43½ lks. dist., with healed, double blaze.</p> <p style="padding-left: 40px;">A white oak, 12 ins. diam., bears N. 60° W., 18½ lks. dist., with healed, double blaze.</p> <p>From this point, United States Coast and Geodetic Survey triangulation station "TWO OAKS" bears S. 31° 44' 00" W., 91.750 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with a 3½ in. diam. brass cap mkd. TWO OAKS 1942.</p>
	<p>From the E 1/16 sec. cor. of secs. 6 and 31, on the S. bdy. of the Tp.</p> <p>N. 0° 10' 00" W., on the N. and S. center line of the SE¼ of sec. 31.</p> <p>Ascend over SE. slope, through heavy timber and dense undergrowth.</p>
9.75	Ridge, bears N. 60° E. and S. 50° W.; desc. over NE. slope.
15.00	Ravine, drains N. 65° W.; asc. over SW. slope.
18.15	Spur, slopes N. 75° W.; desc. over NW. slope.
20.075	<p>Point for the SE 1/16 sec. cor. of sec. 31, at intersection with the E. and W. center line of the SE¼.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 31 1987</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 64° E., 20 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 23° E., 15 lks. dist., mkd. SE 1/16 S31 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Descend over NW. slope.</p>
21.25	Ravine, drains N. 80° W.; asc. over broken SW. slope.
26.85	Spur, slopes N. 70° W.; desc. over broken NW. slope.
36.30	Spur, slopes N. 35° W.; desc. over NE. slope.
40.160	The center E 1/16 sec. cor. of sec. 31.
	<p>From the S 1/16 sec. cor. fo secs. 31 and 32.</p> <p>N. 89° 58' 00" W., on the E. and W. center line of the SE¼ of sec. 31.</p>