

County Surveyor's Record, Douglas County, Oregon

18416 Dependent Resurvey of a Portion of the East Boundary,
T. 26 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

(Restoring the survey by Dennis Hathorn in 1855, the resurvey by Addison R. and Samuel C. Flint in 1881, and the resurvey by Peter A. Peterson and Daniel L. Berry in 1971)

Beginning at the cor. of secs. 1, 6, 7, and 12 on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T 26 S
R 8 W R 7 W
S 1 | S 6
S 12 | S 7
1971

*Fd 8/90
M 110-55
G. B. B. (M. 20)*

from which bearing trees mkd. by Peterson and Berry

A madrone, 6 ins. diam., bears S. 81½° E., 27 lks. dist., with healed blaze.

A fir, 19 ins. diam., bears S. 7½° E., 39 lks. dist., with healed blaze.

A fir, 25 ins. diam., bears S. 37½° W., 73 lks. dist., with healed blaze.

and bearing trees mkd. by Jelley and Rogers

A fir, 9 ins. diam., bears N. 9° E., 36½ lks dist., with fragmentary scribe marks visible on partially healed blaze.

A fir, 7 ins. diam., bears N. 37 3/4° W., 53 lks. dist., with scribe mark X visible on partially healed double blaze.

N. 0° 07' 00" W., bet. secs. 1 and 6, marking and blazing the true line.

Descend over NW. slope, through heavy timber and dense undergrowth.

4.00 Bottom of descent, drains N. 60° W.; asc. over SW. slope.

38.40 Top of descent, slopes N. 70° W.; desc. over NW. slope.

40.250 The ¼ sec. cor. of secs. 1 and 6, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

¼
S 1 | S 6
T 26 S
R 8 W R 7 W
1971

*Fd 8/90
M 110-55*

from which the remains of bearing trees mkd. by Peterson and Berry

A sawed fir stump, 15 ins. diam., bears N. 43° E., 27 lks. dist., with healed blaze. (Record, N. 33° E.)

A fir, 22 ins. diam., bears S. 42° E., 26 lks. dist., with healed blaze.

and a new bearing tree

A fir, 29 ins. diam., bears N. 69° W., 106 lks. dist., Mkd. ¼ S1 BT.