

# County Surveyor's Record, Douglas County, Oregon

18417

T. 26 S., R. 8 W., Willamette Meridian, Oregon

**CHAINS**

Land, mountainous.  
Soil, rocky clay.  
Timber, fir, cedar, hemlock, yew, maple, dogwood, willow, alder, madrone, cherry, pine, and ash; undergrowth, poison oak, blackberry, manzanita, Oregon grape, salal, thimbleberry, rhododendron, salmonberry, arrowwood, hazel, ferns huckleberry, and young timber.

Subdivision of Section 1,  
T. 26 S., R. 8 W., Willamette Meridian, Oregon

From the  $\frac{1}{4}$  sec. cor. of secs. 1 and 12, monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

$\frac{1}{4}$   $\frac{S\ 1}{S\ 12}$   
T 26 S R 8 W  
1983  
1971

*Fd 8/90  
M 110-55  
S. Hoffmann*

from which a bearing tree mkd. by Peterson and Berry

A fir, 8 ins. diam., bears S.  $20\frac{1}{4}^\circ$  E., 33 lks. dist., with healed blaze.

and a bearing tree mkd. by Jelley and Rogers

A fir, 7 ins. diam., bears N.  $37\frac{1}{4}^\circ$  W., 50 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

N.  $1^\circ 07' 00''$  W., on the N. and S. center line of sec. 1, marking and blazing the true line.

Ascend over SE. slope, through heavy timber and dense undergrowth.

- 0.65 Spur, slopes N.  $50^\circ$  E., desc. over broken NE. slope.
  - 4.25 Creek, 2 lks. wide, course N.  $55^\circ$  E.; asc. over SE. slope.
  - 11.70 Spur, slopes S.  $85^\circ$  E.; desc. over broken NE. slope, changing to NW. slope.
  - 21.55 Gravelled road, 40 lks. wide, bears N.  $70^\circ$  W. and S.  $70^\circ$  E.
  - 24.30 East edge of gravelled road, 40 lks. wide, bears N.  $40^\circ$  W. and S.  $40^\circ$  W., in curve.
  - 28.05 East edge of gravelled road, 40 lks. wide, bears N.  $40^\circ$  W. and S.  $10^\circ$  W., in a curve.
  - 40.310 Point for the center  $\frac{1}{4}$  sec. cor. of sec. 1, at intersection with the E. and W. center line.
- Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T 26 S R 8 W  
C  $\frac{1}{4}$   
S 1  
1987

from which

*FD OK 5/91  
BY E. FARR  
1998-0103*

*Fd 8/90  
M 110-55  
R. Hoffmann  
M 113-48*

*FD OK  
5/97  
R. Quimby  
M 126-80*