

County Surveyor's Record, Douglas County, Oregon

18448

Subdivision of Section 1,
T. 26 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 7 ins. diam., bears N. 66° E., 34 lks. dist., mkd. C$\frac{1}{4}$ S1 BT.</p> <p>A fir, 15 ins. diam., bears S. 5° W., 17 lks. dist., mkd. C$\frac{1}{4}$ S1 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Descend over NW. slope.</p>
41.60	<p>Bear Creek, 15 lks. wide, course N. 70° E.; asc. over broken SE. slope.</p>
42.879	<p>A point established by Roderick R. Kimberling, Registered Land Surveyor No. 1903, in 1983, monumented with an iron rod, 5/8 in. diam., firmly set, projectin 4 ins. above ground, with brass washer mkd. LS 1903.</p>
60.660	<p>Point for the center N 1/16 sec. cor. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>C N 1/16 S 1 C 1987</p> </div> <p>from which</p> <p>A fir, 7 ins. diam., bear N. 5° E., 46 lks. dist., mkd. CN 1/16 S1 BT.</p> <p>A hemlock, 9 ins. diam., bears N. 31$\frac{1}{2}$° W., 11$\frac{1}{2}$ lks. dist., mkd. CN 1/16 S1 BT.</p> <p>Deposit a white "DEEP - 1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, Douglas County Surveyor's Office horizontal control station "GREEN BUTTE", bears S. 69° 40' 15" E., 185.437 chs. dist., monumented with a brass disk, 2$\frac{1}{2}$ ins. diam., cemented into bedrock, mkd. DOUGLAS COUNTY SURVEYORS OFFICE GREEN BUTTE 1971.</p> <p>Ascend over broken SE. slope.</p>
77.45	<p>Spur, slopes N. 60° E.; desc. over NE. slope.</p>
80.650	<p>The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE T 25 S $\frac{1}{4}$ $\frac{S 36}{S 1}$ R T 26 S W 1971</p> </div> <p>from which the remains of an original bearing tree</p> <p>A sawed fir stump, 30 ins. diam., bears S. 35° E., 40 lks. dist., with fragmentary scribe marks visible on bark blaze.</p>