

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 1,
T 26 S., R. 8 W., Willamette Meridian, Oregon

18449

CHAINS													
	<p>and bearing trees mkd. by Vernon R. Tracy, Deputy County Surveyor, in 1971</p> <p style="padding-left: 40px;">A cedar, 15 ins. diam., bears N. 87° E., 43 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A hemlock, 20 ins. diam., bears S. 67° W., 76 lks. dist., with healed double blaze.</p>												
19.725	<p>From the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp. N. 89° 26' 00" W., on the E. and W. center line of sec. 1.</p> <p>Descend over NW. slope, through heavy timber and dense undergrowth.</p> <p>Point for the center E 1/16 sec. cor. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td></td><td style="text-align: center;">E 1/16</td><td></td></tr> <tr><td style="text-align: center;">C</td><td style="text-align: center;">S 1</td><td style="text-align: center;">C</td></tr> <tr><td></td><td style="text-align: center;">1987</td><td></td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears N. 28° E., 41 lks. dist., mkd. CE 1/16 S1 BT.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 63° E., 51 lks. dist., mkd. X BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>		E 1/16		C	S 1	C		1987				
	E 1/16												
C	S 1	C											
	1987												
26.05	Hubbard Creek, 15 lks. wide, course N. 15° W.; asc. over NE. slope.												
27.20	Hubbard Creek Road, paved, 40 lks. wide, bears N. 15° E. and S. 20° W.												
39.00	Spur, slopes N. 25° E.; desc. over NW. slope.												
39.450	<p>The center $\frac{1}{4}$ sec. cor. of sec. 1.</p> <p>Descend over NW. slope.</p>												
46.60	Bear Creek, 25 lks. wide, course N. 30° E.; asc. over precipitous SE. slope.												
69.25	Spur, slopes S. 20° E.; desc. over steep SW. slope.												
77.05	Cole Creek, 25 lks. wide, course S. 30° E.; asc. over precipitous NE. slope.												
78.380	<p>The $\frac{1}{4}$ sec. cor. of sec. 1 only, monumented with an iron post, 2½ ins. diam, firmly set, projecting 12 ins. above ground, in a stone collar, 1 ft. base, 1 ft. high, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td style="text-align: center;">RESET</td><td style="text-align: center;"> </td><td style="text-align: center;">$\frac{1}{4}$</td></tr> <tr><td style="text-align: center;">1983</td><td style="text-align: center;"> </td><td style="text-align: center;">S 1</td></tr> <tr><td style="text-align: center;">T 26 S</td><td style="text-align: center;"> </td><td style="text-align: center;">R 8 W</td></tr> <tr><td></td><td style="text-align: center;"> </td><td style="text-align: center;">1971</td></tr> </table> </div> <p>from which the remaining bearing tree mkd. by Peterson and Berry</p> <p style="padding-left: 40px;">A fir, 34 ins. diam., bears S. 44° E., 121 lks. dist., with healed blaze.</p>	RESET		$\frac{1}{4}$	1983		S 1	T 26 S		R 8 W			1971
RESET		$\frac{1}{4}$											
1983		S 1											
T 26 S		R 8 W											
		1971											