

# County Surveyor's Record, Douglas County, Oregon

18451

Subdivision of Section 1,  
T. 26 S., R.8 W., Willamette Meridian, Oregon

CHAINS

From the N 1/16 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

N 1/16  
S 1 | S 6  
1971

from which the remains of bearing trees mkd. by Peterson and Berry

A sawed fir stump, 20 ins. diam., bears N. 71° E.,  
36 lks. dist., with healed blaze.

A sawed fir stump, 18 ins. diam., bears N. 30° W.,  
46 lks. dist., with fragmentary scribe marks visible  
on partially healed blaze. (Record, N. 36° W.)

and a new bearing tree

A fir, 10 ins. diam., bears N. 12¼° W., 29 lks. dist.,  
mkd. N 1/16 S1 BT.

No suitable trees available in sec. 6.

N. 89° 11' 00" W., on the E. and W. center line of the NE¼ of  
sec. 1.

Descend over NW. slope, through heavy timber and dense undergrowth.

19.950 The NE 1/16 sec. cor. of sec. 1.

Descend over NW. slope.

21.20 Hubbard Creek, 30 lks. wide, course N. 10° W.; asc. over broken  
SE. slope.

23.95 Hubbard Creek Road, paved, 40 lks. wide, bears N. and S.

24.85 East edge of pond, edge bears N. and S.

31.05 West edge of pond, edge bears N. 40° E. and S. 10° E.

39.870 The center N 1/16 sec. cor. of sec. 1

From the E 1/16 sec. cor. of secs. 1 and 12, monumented with an  
iron post, 2½ ins. diam., firmly set, projecting 4 ins. above  
ground, with brass cap mkd.

E 1/16      S 1  
              S 12  
              1971  
              1983

from which a bearing tree mkd. by Peterson and Berry

A grand fir, 13 ins. diam., bears S. 84½° W.,  
49½ lks. dist., with healed blaze.

and a bearing tree mkd. by Jelley and Rogers

A fir, 16 ins. diam., bears N. 53½° E., 37½ lks. dist.,  
with fragmentary scribe marks visible on partially  
healed blaze.

N. 0° 35' 00" W., on the N. and S. center line of the SE¼ of sec.  
1.

Descend over broken NW. slope, through heavy timber and dense  
undergrowth.