

County Surveyor's Record, Douglas County, Oregon

18452

Dependent Resurvey of a Portion of the South Boundary,
T. 21 S., R. 6 W., Willamette Meridian, Oregon

CHAINS													
21.30	Dirt road, 15 lks. wide, bears N. 60° W. and S. 60° E.												
33.10	Same dirt road, 15 lks. wide, bears N. 80° E. and S. 80° W.												
38.880	Point for the $\frac{1}{4}$ sec. cor. of sec. 6 only, T. 22 S., R. 6 W., at proportionate distance; there is no remaining evidence of the original corner. No permanent monument established.												
40.140	Point for the $\frac{1}{4}$ sec. cor. of sec. 31 only. Set a stainless steel post, 28 ins. ling, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 21 S</td><td>R 6 W</td></tr> <tr><td>$\frac{1}{4}$ S 31</td><td></td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">1987</td></tr> </table> </div> from which A fir, 15 ins. diam., bears N. 23° E., $9\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S31 BT. A fir, 7 ins. diam., bears N. $72\frac{1}{2}$ ° W., $84\frac{1}{2}$ lks. dist., mkd. X BT. Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post. Begin descent over steep broken NW. slope.	T 21 S	R 6 W	$\frac{1}{4}$ S 31		1987							
T 21 S	R 6 W												
$\frac{1}{4}$ S 31													
1987													
40.60	Abandoned dirt road, 20 lks. wide, bears NW. and SE.												
60.70	Creek, 2 lks. wide, course N. 55° E.; asc. over steep NE. slope.												
68.60	Spur, slopes N.; desc. over steep NW. slope.												
77.770	The cor. of Tps. 21 and 22 S., Rs 6 and 7 W., monumented with a stainless steel post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 21 S</td><td></td></tr> <tr><td>R 7 W</td><td>R 6 W</td></tr> <tr><td>S 36</td><td>S 31</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">S 1 S 6</td></tr> <tr><td>T 22 S</td><td></td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">1986</td></tr> </table> </div> from which the remains of the original bearing trees A fir snag, 28 ins. diam., bears N. 59° E., 57 lks. dist., with fragmentary scribe marks visible on opened blaze. A cedar, 38 ins. diam., bears S. 68° W., 14 lks. dist., with a burnt blaze. and the bearing trees mkd. by Vernon R. Tracy, Deputy County Surveyor, in 1966 A hemlock, 14 ins. diam., bears N. 80° E., 36 lks. dist., with healed blaze. A cedar, 27 ins. diam., bears S. $59\frac{1}{2}$ ° E., 45 lks. dist., with healed blaze. A hemlock, 14 ins. diam., bears N. 27° W., 19 lks. dist., with healed blaze.	T 21 S		R 7 W	R 6 W	S 36	S 31	S 1 S 6		T 22 S		1986	
T 21 S													
R 7 W	R 6 W												
S 36	S 31												
S 1 S 6													
T 22 S													
1986													