

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the West Boundary, 18463  
 T. 21 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">(Restoring the survey by Laban H. Wheeler in 1883)</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of Tps. 21 and 22 S., Rs 6 and 7 W.</p> <p>N. 0° 36' 00" E., bet. secs. 31 and 36.</p> <p>Descend over broken NW. slope, through heavy timber and dense undergrowth.</p>
39.150	<p>The ¼ sec. cor. of secs. 31 and 36, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1960, and further perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1972, monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 3 ins. above ground, with washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which the remains of an original bearing tree:</p> <p style="padding-left: 40px;">A rotted fir stump, 16 ins. diam., bears S. 30° E., 5 lks. dist., no marks remaining.</p> <p>and bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A rotted fir stump, size indeterminate, bears N. 53° E., 38½ lks. dist., no marks remaining.</p> <p style="padding-left: 40px;">A hemlock, 18 ins. diam., bears N. 31° W., 25 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by Powell</p> <p style="padding-left: 40px;">A hemlock, 14 ins. diam., bears S. 54° E., 36 lks. dist., with scribe marks ¼ S31 CS visible on a partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 21 S</p> <p>R 7 W R 6 W</p> <p style="margin: 0 10px;">¼</p> <p>S 36   S 31</p> <p>1987</p> </div> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 1° 11' 00" E., beginning new measurement.</p> <p>Descend over gentle NW. slope, through heavy timber and dense undergrowth.</p>
7.30	<p>Bottom of descent, drains NW.; asc. over steep SW. slope.</p>
14.90	<p>Spur, slopes W.; desc. over steep NW. slope, through dense undergrowth.</p>
33.20	<p>Big Tom Folley Creek, 30 lks. wide, course S. 70° W.; asc. over SE. slope.</p>
35.20	<p>Gravelled road, 30 lks. wide, bears N. 60° E. and S. 60° W.</p>

FNO. OK  
 D. BAKER 12/91  
 M 114-26