

County Surveyor's Record, Douglas County, Oregon

18161

Dependent Resurvey of a Portion of the West Boundary
T. 21 S., R. 6 W., Willamette Meridian, Oregon

CHAINS																					
35.80	Dirt road, 20 lks. wide, bears N. 50° E. and S. 50° W.																				
38.910	<p>The cor. of secs. 25, 30, 31, and 36, reestablished by proportionate measurement and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1960, and perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1972; there is no remaining evidence of the original corner, therefore this position is accepted as the corner; monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 6 ins. above ground, with washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which the remains of bearing trees mkd. by Haines:</p> <ul style="list-style-type: none"> ✓ A hemlock, 18 ins. diam., bears S. 81° E., 63 lks. dist., with scribe mark 1 visible on partially healed blaze. A fir, 41 ins. diam., bears N. 71° W., 80 lks. dist., with healed blaze. A fir stump, 36 ins. diam., bears N. 39½° W., 90 lks. dist., no remaining marks. <p>and the remains of bearing trees mkd. by Powell</p> <ul style="list-style-type: none"> A fir, 11 ins. diam., bears S. 28° E., 55 lks. dist., with healed blaze. A rotted fir stump, 8 ins. diam., bears S. 20° W., 18 lks. dist., no remaining marks. <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="4">T 21 S</td></tr> <tr><td colspan="2">R 7 W</td><td colspan="2">R 6 W</td></tr> <tr><td colspan="2">S 25</td><td colspan="2">S 30</td></tr> <tr><td colspan="2">S 36</td><td colspan="2">S 31</td></tr> <tr><td colspan="4">1987</td></tr> </table> </div> <p>from which new bearing trees</p> <ul style="list-style-type: none"> A fir, 11 ins. diam., bears N. 18° E., 26 lks. dist., mkd. T21S R6W S30 BT. ✓ A fir, 10 ins. diam., bears S. 58° W., 27 lks. dist., mkd. T21S R7W S36 BT. <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>	T 21 S				R 7 W		R 6 W		S 25		S 30		S 36		S 31		1987			
T 21 S																					
R 7 W		R 6 W																			
S 25		S 30																			
S 36		S 31																			
1987																					
0.70	N. 0° 57' 00" E., bet. secs. 25 and 30.																				
19.400	<p>Ascend over broken SW. slope, through heavy timber and dense undergrowth.</p> <p>Dirt road, 35 lks. wide, on a curve, bears N. 70° E. and N. 50° W.</p> <p>The S 1/16 sec. cor. of secs. 25 and 30 established and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1960, and is accepted as the corner; monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 3 ins. above ground, with washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which a bearing tee mkd. by Haines:</p> <ul style="list-style-type: none"> A fir, 11 ins. diam., bears S. 20° E., 7½ lks. dist., with healed blaze. 																				

FND. OK
 D. BAKER 12/91
 M 114-26