

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the West Boundary, **18167**
T. 21 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

38.750

The $\frac{1}{4}$ sec. cor. of secs. 19 and 24, reestablished by proportionate measurement and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, ^{in 1960} there is no remaining evidence of the original corner, therefore this position is accepted as the corner; monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 4 ins. above ground, with washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN ORE, from which the bearing trees mkd. by Haines:

A fir, 52 ins. diam., bears N. 17° E., 62 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on the bark.

A fir, 22 ins. diam., bears S. 50° E., 28 lks. dist., with healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, directly over the iron rod, with brass cap mkd.

T 21 S
R 7 W R 6 W
 $\frac{1}{4}$
S 24 | S 19
1987

from which a new bearing tree

A fir, 16 ins. diam., bears S. 81° W., 10 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S24 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

N. 0° 36' 00" E., beginning new measurement.

Ascend over SE. slope.

1.10 Spur, slopes E.; desc. over NE. slope.

6.50 Ravine, drains N. 60° E.; asc. over broken SE. slope.

13.10 Spur, slopes N. 60° E.; desc. over steep N. slope.

19.10 Creek, 15 lks. wide, course N. 40° E.; asc. over broken SE. slope.

25.30 Spur, slopes N. 80° E.; desc. over NE. slope.

29.50 Ravine, drains S. 80° E., asc. over broken SE. slope.

38.720 The cor. of secs. 13, 18, 19, and 24, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1961, monumented with an iron post, 1 $\frac{1}{2}$ ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 21 S
S 13 | S 18
S 24 | S 19
R 7 W R 6 W
1961

from which an original bearing tree

A fir, 45 ins. diam., bears N. 13° E., 45 lks. dist., with fragmentary scribe marks.

and the remains of bearing trees mkd. by Godfrey