

County Surveyor's Record, Douglas County, Oregon

18168 Dependent Resurvey of a Portion of the West Boundary,
T 21 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

A split fir snag, size indeterminate bears S. 25½° E.,
43 lks. dist., with healed blaze.

A fir, 29 ins. diam., bears S. 29½° W., 87 lks. dist.,
with healed blaze.

A fir, 38 ins. diam., bears S. 85 3/4° W., 90 lks. dist.,
with healed blaze.

The corner is on a rock bluff, facing S.

(Restoring the survey by, William H. Byars in 1871, the
survey by William P. Wright in 1884, and the
remonumentation by James E. Jelley in 1979)

From the cor. of secs. 26, 27, 34, and 35, perpetuated and
recorded by Wilford N. Haines, Registered Land Surveyor No. 239,
in 1958, monumented with an iron rod, 24 ins. long, ½ in. diam.,
set 14 ins. in the ground, of which I find no record (with a "T"
shaped iron rod, 36 ins. long, 1 in diam., lying alongside, with
a metal washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE)
from which the remains of the original bearing trees:

A root hole, bears S. 18° E., 19 lks. dist., with a fir,
24 ins. diam., lying alongside, with healed blaze.

A root hole, bears N. 10° W., 15 lks. dist., with a fir,
19 ins. diam., lying alongside, with healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T	21	S	R	6	W
	S	27	S	26	
	S	34	S	35	
					1987

from which new bearing trees

A fir, 11 ins. diam., bears N. 79° E., 15 lks. dist.,
mkd. T21S R6W S26 BT.

A fir, 6 ins. diam., bears S. 48½° E., 21 lks. dist.
mkd. X BT.

A fir, 10 ins. diam., bears S. 41° W., 19 lks. dist.,
mkd. T21S R6W S34 BT.

A fir, 5 ins. diam., bears N. 32° W., 13 lks. dist.,
mkd. X BT.

Deposit the iron rods alongside the stainless steel post.

S. 88° 09' 00" W., bet. secs. 27 and 34.

Ascend over broken SE. slope, through heavy timber and dense
undergrowth.

33.40

Spur, slopes S.; desc. over W. slope.

40.570

Point for the ¼ sec. cor. of secs. 27 and 34, at proportionate
distance; there is no remaining evidence of the original corner.