

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines **18471**
T 21 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	<p>A fir, 50 ins. diam., bears S. 74° W., 53 lks. dist., with healed blaze. (Record, S. 73° W., 51 lks.)</p>									
	<p>S. 89° 01' 00" W., bet. secs. 30 and 31.</p> <p>Ascend over NE. slope, through heavy timber and dense undergrowth.</p>									
0.90	Spur, slopes N. 50° E.; desc. over NW. slope.									
4.10	Ravine, drains N. 35° E.; asc. over NE. slope.									
6.20	Spur, slopes N.; desc. over steep, broken NW. slope.									
12.30	Bottom of steep descent; continue to desc. over broken SW. slope.									
39.920	<p>The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, reestablished by proportionate measurement and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1964; there is no remaining evidence of the original corner, therefore this position is accepted as the corner; monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 4 ins. above ground, with washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE. from which the bearing trees mkd. by Haines:</p> <p style="margin-left: 40px;">A hemlock, 13 ins. diam., bears S. 62° E., 15 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A hemlock, 15 ins. diam., bears N. 45° W., 7 lks. dist. with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 21 S R 6 W</p> <table style="margin: auto; border: none;"> <tr> <td style="padding: 0 10px;">$\frac{1}{4}$</td> <td style="border: none; padding: 0 5px;">S</td> <td style="border: none; padding: 0 5px;">30</td> </tr> <tr> <td style="border: none;"></td> <td style="border: none; padding: 0 5px;">S</td> <td style="border: none; padding: 0 5px;">31</td> </tr> <tr> <td style="border: none;"></td> <td style="border: none;"></td> <td style="border: none; padding: 0 10px;">1987</td> </tr> </table> </div> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 01' 00" W., beginning new measurement.</p> <p>Descend over broken SW. slope.</p>	$\frac{1}{4}$	S	30		S	31			1987
$\frac{1}{4}$	S	30								
	S	31								
		1987								
15.80	Creek, 5 lks. wide, course N. 20° E., curving NW.; asc. over NE. slope.									
20.80	Spur, slopes N. 10° E.; desc. over NW. slope.									
25.40	Big Tom Folley Creek, 45 lks. wide, course S. 60° W.; asc. over broken SE. slope.									
28.20	Gravelled road, 30 lks. wide, bears N. 60° E. and S. 60° W.									
32.80	Dirt road, 20 lks. wide, bears N. 20° E. and S. 20° W.									
35.80	Spur, slopes S.; desc. over SW. slope.									
36.510	The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp.									