

County Surveyor's Record, Douglas County, Oregon

18175

T. 25 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

Dependent Resurvey of a Portion of the South boundary,
T. 25 S., R. 3 W., Willamette Meridian, Oregon

(Restoring the survey by Addison R. Flint in 1855, and
the resurvey by Norman D. Price in 1943-44)

Beginning at the cor. of secs. 4, 5, 32, and 33, on the S. bdy.
of the Tp. monumented with an iron post, 2 ins. diam., firmly
set, projecting 8 ins. above ground, with brass cap mkd.

T 25 S	R 3 W
S 32	S 33
S 5	S 4
T 26 S	
1943	

from which an original bearing tree

A fir, 57 ins. diam., bears N. 25° E., 24 lks. dist.,
with partial bark scribing visible.

and the remains of a bearing tree mkd. by Ben B. Irving, Deputy
County Surveyor in 1930

A root hole, bears N. 20° W., 27 lks. dist., with a down
yew alongside, 11 ins. diam., with partially healed,
rotted blaze.

and the remains of bearing trees mkd. by Price

A rotted, sawed yew stump, 9 ins. diam., bears N. 37½° E.,
54 lks. dist., no marks visible.

A rotted, sawed fir stump, 45 ins. diam., bears S. 76° E.,
73 lks. dist., with fragmentary scribe marks R3W S BT
visible on opened blaze.

A root hole, bears S. 62° W., 15 lks. dist., with a down
yew alongside, 12 ins. diam., with partially healed
rotted blaze.

and the remains of a bearing tree mkd. by Vernon R. Tracy, Deputy
County Surveyor, in 1966

A sawed fir stump, 18 ins. diam., bears S. 24° E.,
67½ lks. dist., with healed blaze.

and new bearing trees

A fir, 6 ins. diam., bears S. 21° E., 29 lks.
dist., mkd. T26S R3W S4 BT.

A fir, 9 ins. diam., bears S. 45 3/4° W., 60 lks.,
dist., mkd. T26S R3W S5 BT.

A fir, 6 ins. diam., bears N. 59° W., 33 lks. dist.
mkd. T25S R3W S32 BT.

N. 89° 14' 00" W., bet. secs. 5 and 32.

Descend over NW. slope, through heavy timber and dense
undergrowth.

3.80 Creek, 4 lks. wide, course S. 55° W.; asc. over SE. slope.

11.50 Spur, slopes SW.; desc. over NW. slope.