

County Surveyor's Record, Douglas County, Oregon

18476

Dependent Resurvey of a Portion of the South Boundary,
T. 25 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

17.70 Creek, 20 lks. wide, course S. 20° W.; asc. over W. slope.

20.300 Point for the E 1/16 sec. cor. of secs. 5 and 32.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

E 1/16 $\frac{S\ 32}{S\ 5}$
1988

from which

A white fir, 12 ins. diam., bears N. 73° E., 26 lks. dist., mkd. E 1/16 S32 BT.

A fir, 11 ins. diam., bears S. 43° E., 28 lks. dist., mkd. E 1/16 S5 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

The corner is located on a SE. slope, with a down E-W fence alongside.

Ascend over SE. slope.

22.50 Spur, slopes S. 20° W.; desc. over W. slope.

23.95 Ravine, drains S.; asc. over broken E. slope.

25.35 Top of ascent on S. slope; desc. over broken W. slope.

39.80 Gravelled road, 15 lks. wide, bears N. 15° E. and S. 20° W.

40.600 The ¼ sec. cor. of secs. 5 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.

¼ $\frac{S\ 32}{S\ 5}$
1943

from which a bearing tree mkd. by Bruce R. Rogers, Deputy County Surveyor, in 1965

A white oak, 10 ins. diam., bears N. 44½° W., 45 lks. dist., with healed blaze.

and a new bearing tree

A ponderosa pine, 15 ins. diam., bears S 85° E., 15 lks. dist., mkd. ¼ S5 BT.

The corner is located on SW. slope.

Dependent Resurvey of a Portion of the North Boundary,
T. 25 S., R. 3 W., Willamette Meridian, Oregon

(Restoring the survey by William H. Byars in 1871, and
the resurvey by Norman D. Price in 1943-44)

From the cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.