

County Surveyor's Record, Douglas County, Oregon

18480

Dependent Resurvey of a Portion of the North Boundary,
T. 25 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

A madrone, 28 ins. diam., bears S. $67\frac{1}{4}^{\circ}$ W., 73 lks. dist., no marks visible on decayed, opened blaze.

and the remains of bearing trees mkd. by Arthur Boyer, Deputy County Surveyor, in 1941.

A fir snag, size indeterminate, bears S. $51\frac{3}{4}^{\circ}$ E., 27 lks. dist., no marks visible.

A fir, 44 ins. diam., bears N. $26\frac{1}{4}^{\circ}$ W., 48 lks. dist., with healed blaze.

and bearing trees mkd. by Vernon R. Tracy, Deputy County Surveyor, in 1966.

A chinquapin, 12 ins. diam., bears N. $83\frac{3}{4}^{\circ}$ E., 29 lks. dist., with fragmentary marks visible on partially healed double blaze.

A madrone, 7 ins. diam., bears S. 27° E., 32 lks. dist., with fragmentary marks visible on partially healed double blaze.

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 25 S., R. 3 W., Willamette Meridian, Oregon

(Restoring the survey by Laban H. Wheeler in 1883,
and the resurvey by Norman D. Price in 1943-44)

From the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.

$\frac{1}{4}$
S 3 | S 2
1944

from which the remains of a bearing tree mkd. by Price

The base of a tipped over hemlock snag, 25 ins. diam., bears N. 78° W., 10 lks. dist., no marks visible.

and the bearing trees mkd. by Vernon R. Tracy, Deputy County Surveyor, in 1966

A maple, 8 ins. diam., bears S. 21° E., 26 lks. dist., with healed blaze.

A fir, 15 ins. diam., bears S. 9° W., 19 lks. dist., with healed blaze.

and new bearing trees

A fir, 8 ins. diam., bears N. 17° E., 15 lks. dist., mkd. $\frac{1}{4}$ S2 BT.

A fir, 10 ins. diam., bears S. 33° W., 25 lks. dist., mkd. $\frac{1}{4}$ S3 BT.

The corner is 50 lks. W. of a gravelled road, 20 lks. wide, bears N. 30° W. and S.

N. $9^{\circ} 18' 00''$ W., bet. secs. 2 and 3.