

County Surveyor's Record, Douglas County, Oregon

18482

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 25 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	N 1/16 S 4 S3 1987
	from which
	A fir, 24 ins. diam., bears N. 88° E., 32½ lks. dist., mkd. N 1/16 S3 BT.
	A cedar, 15 ins. diam., bears S. 12° W., 22 lks. dist., mkd. N 1/16 S4 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Continue over SW. slope.
22.10	Top of ascent; across rocky W. slope.
23.650	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp.
	From the ¼ sec. cor. of secs. 32 and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground with brass cap mkd.
	¼ S 32 S 33 1943
	from which a bearing tree mkd. by Price
	A yew, 10 ins. diam., bears S. 8½° E., 42 lks. dist., with fragmentary scribe marks visible on partially healed blaze.
	and a new bearing tree
	A fir, 12 ins. diam., bears N. 50° W., 50 lks. dist., mkd. ¼ S32 BT.
	N. 1° 18' 00" E., bet. secs. 32 and 33.
	Ascend over SW. slope, through heavy timber and dense undergrowth
3.80	Spur, slopes N. 85° W.; desc. over NW. slope.
10.05	Dirt road, 25 lks. wide, bears N. 20° W. and S. 10° W.
19.050	Point for the N 1/16 sec. cor. of secs. 32 and 33.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam. 20 ins. in the ground, with brass cap mkd.
	N 1/16 S 32 S 33 1988
	from which
	A fir, 10 ins. diam., bears S. 8° E., 29 lks. dist., mkd. N 1/16 S33 BT.
	A cedar, 20 ins. diam., bears N. 39° W., 38 lks. dist., mkd. N 1/16 S32 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Ascend over broken SW. slope.