

County Surveyor's Record, Douglas County, Oregon

18185

Dependent Resurvey of a Portion of the Subdivisional Lines,
T.25 S., R.3 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">A cedar, 13 ins. diam., bears N. 29° W., 50 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Vernon R. Tracy, Deputy County Surveyor, in 1966</p> <p style="text-align: center;">A cedar, 30 ins. diam., bears S. 58° E., 33 lks. dist., with scribe marks S16 CS BT visible on double blaze.</p> <p style="text-align: center;">A hemlock, 11 ins. diam., bears N. 38° W., 24 lks. dist., with healed blaze.</p>
	<p>N. 1° 26' 00" W., bet. secs. 8 and 9.</p> <p>Descend over broken NE. slope, through heavy timber and dense undergrowth.</p>
6.80	Creek, 10 lks. wide, course NW.; asc. over SW. slope.
8.40	Spur, slopes W.; desc. over NW. slope.
19.995	<p>Point for the S 1/16 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 8 S 9 1987</p> <p>from which</p> <p style="text-align: center;">A fir, 8 ins. diam., bears S. 29° E., 14 lks. dist., mkd. S 1/16 S9 BT.</p> <p style="text-align: center;">A hemlock, 17 ins. diam., bears S. 85½° W., 24 lks. dist., mkd. S 1/16 S8 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Descend over NW. slope.</p>
22.30	Dirt road, 20 lks. wide, bears NE. and SW.
39.990	<p>The ¼ sec. cor. of secs. 8 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">¼ S 8 S 9 1944</p> <p>from which the remaining original bearing tree</p> <p style="text-align: center;">A fir, 40 ins. diam., bears N. 55° E. 21 lks. dist., with healed blaze and rescribed by Arthur Boyer, Deputy County Surveyor, in 1939, with scribe marks ¼ S9 T25S R3W CS BT visible on bark blaze.</p> <p>and a bearing tree mkd. by Arthur Boyer, Deputy County Surveyor, in 1939</p> <p style="text-align: center;">A maple, 24 ins. diam., bears S. 77° W., 55 lks. dist., with healed blaze. (Record, S. 74½° W., 50 lks.)</p> <p>and bearing trees mkd. by Vernon R. Tracy, Deputy County Surveyor, in 1966</p>