

# County Surveyor's Record, Douglas County, Oregon

18486

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 25 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	<p>A grand fir, 12 ins. diam., bears N. 18° E., 60 lks. dist., with healed double blaze.</p> <p>A cedar, 16 ins. diam., bears S. 33° W., 36 lks. dist., with healed double blaze.</p>
	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 31 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <math>\frac{1}{4}</math>                      S 31   S 32                      1943                 </div> <p>from which the remains of bearing trees mkd. by Price</p> <p>A sawed fir stump, 16 ins. diam., bears S. 11° E., 63 lks. dist., with scribe marks BT visible on open blaze.</p> <p>A sawed fir stump, 19 ins. diam., bears S. 4° W., 109 lks. dist., with scribe marks <math>\frac{1}{4}</math> visible on partially healed blaze.</p> <p>and bearing trees mkd. by Bruce R. Rogers, Deputy County Surveyor, in 1965</p> <p>An oak, 15 ins. diam., bears S. 22° E., 38 lks. dist., with healed double blaze.</p> <p>An oak, 8 ins. diam., bears S. 62° W., 43 lks. dist., with healed double blaze.</p> <p>N. 0° 50' 00" E., bet. secs. 31 and 32.</p> <p>Ascend along SW. slope, through scattered timber and dense undergrowth.</p>
23.010	<p>Point for the N 1/16 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">                     N 1/16                      S 31   S32                      1988                 </div> <p>from which</p> <p>A fir, 14 ins. diam., bears S. 30° E., 154 lks. dist., mkd. N 1/16 S32 BT.</p> <p>A fir, 14 ins. diam., bears N. 45° W., 110 lks. dist., mkd. N 1/16 S31 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>An iron fence post is alongside the corner.</p> <p>Ascend over SW. slope.</p>
28.60	<p>Spur, slopes W.; desc. over NW. slope.</p>
32.60	<p>Ravine, drains SW.; asc. over SW. slope.</p>
46.020	<p>The cor. of secs. 29, 30, 31, and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p>