

# County Surveyor's Record, Douglas County, Oregon

18488

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 25 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

from which

A cedar, 20 ins. diam., bears N. 20° E., 7½ lks. dist.,  
mkd. E 1/16 S29 BT.

A hemlock, 19 ins. diam., bears S. 85½° W., 80½ lks. dist.,  
mkd. E 1/16 S32 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the  
stainless steel post.

The corner is located on the S. edge of a swampy area.

Ascend over gentle E. slope.

23.80 Leave swamp, edge bears N. 5° E. and S. 40° W.

27.80 Spur, slopes S. 20° W.; desc. over SW. slope.

33.75 Creek, 5 lks. wide, course S. 5° W.; asc. over SE. slope.

40.860 The ¼ sec. cor. of sec. 29 and 32, monumented with an iron post,  
1 in. diam., firmly set, projecting 17 ins. above ground, with  
brass cap mkd.

¼     S 29  
       S 32  
       1943

from which the remains of an original bearing tree

A root hole, bears S. 32½° W., 11 lks. dist., with a  
down fir alongside, 42 ins. diam., with healed blaze.

and a bearing tree mkd. by Price

A cedar, 42 ins. diam., bears N. 68¼° E., 49 lks. dist.,  
with fragmentary scribe marks visible on partially  
healed blaze.

and the remains of a bearing tree mkd. by Vernon R. Tracy, Deputy  
County Surveyor, in 1966

A root hole, bears N. 80° E., 73 lks. dist., with a  
down fir alongside, size indeterminate, with scribe  
marks ¼ S29 BT visible on blaze.

and a new bearing tree

A fir, 9 ins. diam., bears S. 6½° W., 15 lks. dist.,  
mkd. ¼ S32 BT.

Subdivision of Section 3,  
T. 25 S., R. 3 W., Willamette Meridian, Oregon

From the ¼ sec. cor. of secs. 3 and 10, monumented with an iron  
post, 1 in. diam., firmly set, projecting 4 ins. above ground,  
with brass cap mkd.

¼     S 3  
       S 10  
       1944

from which the remains of the original bearing trees

A fir stump, 40 ins. diam., bears N. 37° E., 33 lks.  
dist., with scribe marks ¼ S3 BT visible on opened blaze.