

County Surveyor's Record, Douglas County, Oregon

18491

Subdivision of Section 3,
T. 25 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	$\frac{W \ 1/16}{S \ 3} \ C$ 1987
	from which A cedar, 10 ins. diam., bears N. 58° E., 18 lks. dist., mkd. CW 1/16 S3 BT. A madrone, 10 ins. diam., bears S. 10° E., 15 lks. dist., mkd. CW 1/16 S3 BT. Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
60.50	Spur, slopes S.; desc. over SW. slope.
61.90	Ravine, drains S. 10° E.; asc. over SE. slope.
63.75	Spur, slopes S.; desc. over broken SW. slope.
81.200	The $\frac{1}{2}$ sec. cor. of secs. 3 and 4.
	From the center E 1/16 sec. cor. of sec. 3. N. 10° 08' 00" W., on the N. and S. center line of the NE $\frac{1}{4}$ of sec. 3. Descend over NW. slope, through heavy timber and dense undergrowth.
7.70	Creek, 6 lks. wide, course S. 40° W.; across gentle W. slope.
12.450	Point for the NE 1/16 sec. cor. of sec. 3, at intersection with the E. and W. center line of the NE $\frac{1}{4}$. Set a stainless steel post, 28 ins. long 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	$\frac{NE \ 1/16}{S \ 3}$ 1987
	from which A cedar, 14 ins. diam., bears S. 18° E., 28 lks. dist., mkd. NE 1/16 S3 BT. A fir, 10 ins. diam., bears N. 5° W., 57 lks. dist., mkd. NE 1/16 S3 BT. Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Continue across W. slope.
18.30	Creek, 3 lks. wide, course S. 70° W.; asc. over SE slope.
24.230	The E 1/16 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.
	From the N 1/16 sec. cor. of secs. 2 and 3. S. 89° 03' 00" W., on the E. and W. center line of the NE $\frac{1}{4}$ of sec. 3. Ascend over SE. slope, through heavy timber and dense undergrowth.